

Model	S5800P-24G-2S
Product	Full Gigabit 2SFP+24GE POE Switch
Fixed Port	24*10/100/1000Base-TX PoE port(Data/Power) 2*1000M SFP
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 3-24 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 300W
Bandwidth	56Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	PWR:Power LED(green) 1-24:10/100、1000M Network connection indicator(green) 25-26:SFP connection indicator(green) PoE:PoE indicator(orange)
Function	N:(Standard normal) V:(Port isolation) C:(Flow control mode)
Power	Built-in power AC：100-240Vac 50-60Hz 5A max 415W
Operating Temperature/Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃；5%~95% RH Non coagulation
Product /Packing size(L*W*H)	440mm*290mm*45mm 515mm*375mm*95mm
N.W/G.W(kg)	3.4kg/4.1kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	6KV 8/20us；IP30
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.