



Hardware specifications

Model	S1100P-4F-2FX
Product name	Fast Ethernet 4+2 Fiber PoE Switch
Fixed Port	4*10/100Base-TX PoE port (Data) 2*100M Integrated SFP (optional1310/1550)
PoE Ports	1-4 port supports PoE(optional first port outputs HiPoE_60W)
Network Protocol	IEEE802.3 IEEE802.3i 10BASE-T IEEE802.3u100BASE-TX IEEE802.3x IEEE 802.3z 1000BASE-X IEEE802.3af/at(HiPoE PoE++optional)
Network protocol	IEEE 802.3/U、IEEE 802.3ab、IEEE 802.3bz、IEEE 802.3x
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	1.6Gbps
Packet Forwarding	1.3Mpps
MAC Address	1K
Buffer	768K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) Single mode single fiber(MAX 20km) Single mode double fiber(MAX 20km) Multiple mode double fiber(MAX 850meter/2km) Optional 3-80km SFP
LED Indicator	Power:Power LED 5-6:(Integrated SFP LED) Port:(Orange=PoE LED+Green=Link LED)
Power Pin	Default 1/2(+), 3/6(-); Optional order 4/5(+), 7/8(-)
Single port power	Average 15.4W; MAX 30W
Power Input	Built-in power AC 100~240V 50-60Hz 1A
Watt	Standby Power Consumption: ≤5W;
Operating Temperature /Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	210mm*150mm*35mm 265mm*220mm*68mm
N.W/G.W (kg)	0.7kg/1.1kg
Installation	Desktop(optional wall hanger parts)
Certificate	3C; CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.