

| | |
|-----------------------------------|---|
| Model | F5800-10S-8G |
| Product name | Full Gigabit 10 Fiber Switch |
| Fixed Port | 8*10/100/1000Base-TX RJ45 port (Data) 10*1000M SFP |
| Network protocol | IEEE802.3 IEEE802.3i 10BASE-T IEEE802.3u100BASE-TX IEEE 802.3ab1000BASE-T IEEE802.3x IEEE 802.3z 1000BASE-X |
| Port Specification | 10/100/1000BaseT (X) Auto |
| Transmission Mode | Store and Forward(full wirespeed) |
| Bandwidth | 56Gbps |
| Packet Forwarding | 40.32Mpps |
| MAC | 8K |
| Buffer | 4.1M |
| Transmission Distance | 10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) Optional single mode single fiber(MAX 20KM) Optional single mode double fiber (MAX 20KM) Optional multiple mode double fiber(MAX 850M/2KM) Optional 3-80KM SFP |
| LED Indicator | PWR:Power LED 1~16:(SFP LED) Port:(Green=10/100M LED+Orange=1000M LED) |
| Power | Built-in power AC 100~240V 50/60HZ 1A |
| Watt | Standby Power Consumption: ≤30W |
| Operating Temperature /Humidity | -10~+55°C; 5%~90% RH Non coagulation |
| Storage Temperature /Humidity | -40~+75°C; 5%~95% RH Non coagulation |
| Product size/Packing size (L*W*H) | 440mm*205mm*45mm 515mm*295mm*95mm |
| N.W/G.W (kg) | 2.2kg/3.1kg |
| Installation | Rack-mount(optional machine hanger spare parts) |
| Certificate | CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS |
| Warranty | Whole device for 1 year(Accessories not included) |

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.