

【S1100-4G-2S】
PARAMETER



Front

Back

Model	S1100-4G-2S
Product	All Gigabit 4+2 Ethernet Switch
Fixed Port	4*10/100/1000Base-TX RJ45 port (Data) 2*1000M SFP
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u100BASE-TX IEEE 802.3ab1000BASE-T IEEE 802.3z 1000BASE-X
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward (full wirespeed)
Bandwidth	16Gbps
Packet Forwarding	14.44Mpps
MAC Address	4K
Buffer	2.5M
Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(150 meter) 1000BASE-SX: 62.5μm/50μm MMF(2m~550m) 1000BASE-LX: 62.5μm/50μm MM(2m~550m) or 10μm SMF(2m~5000m)
Watt	≤6W
LED Indicator	PWR:Power LED Port:(Green=10/100M LED+Orange=1000M LED) 5-6:(Gigabit upLink LED)
Power	External Power DC:12V 1A
Operating Temperature/Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	210mm*85mm*28mm 305mm*205mm*55mm
N.W/G.W (kg)	0.4kg/0.7kg
Installation	Desktop (optional Wall hanger)
Lightning protection level	3KV 8/20us; IP30
Certificate	3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)