



【S500-4F-1FX】
PARAMETER



正面



背面

Model	S500-4F-1FX
Product	Fast Ethernet 4+1 Fiber Switch
Fixed Port	4*10/100Base-TX RJ45 port (Data) 1*100M Integrated SFP (optional 1310/1550)
Network Protocol	IEEE802.3 IEEE802.3i 10BASE-T IEEE802.3u100BASE-TX IEEE802.3x IEEE 802.3z 100BASE-X
Port Specification	10/100BaseT (X) Auto
Transmission Mode	Store and Forward (full wirespeed)
Bandwidth	1Gbps
Packet Forwarding	0.72Mpps
MAC Address	1K
Buffer	768K
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) Single mode single fiber(MAX 20KM) Single mode double fiber (MAX 20KM) Multiple mode double fiber(MAX 850M/2KM) Optional 3-80KM SFP
Watt	≤2W
LED Indicator	PW:Power LED 1~4:(Link LED) 5:(Integrated SFP LED)
Power	External Power DC: 12V 0.5A
Operating Temperature/Humidity	-10~+55℃;5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃;5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	88mm*82mm*25mm 105mm*105mm*65mm
N.W/G.W (kg)	0.4kg/0.5kg
Installation	Desktop
Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial;CE/LVD EN60950; FCC Part 15 Class B;RoHS;
Warranty	Whole device for 1 year(Accessories not included)