

|                                       |  |
|---------------------------------------|--|
| Model                                 | S500-5F  |
| Product name                          | 5 Port Fast Ethernet Switch  |
| Fixed Port                            | 5*10/100Base-TX RJ45 port(Data)  |
| Network Protocol                      | IEEE 802.3<br>IEEE 802.3i 10BASE-T<br>IEEE 802.3u 100BASE-TX                     |
| Port Specification                    | 10/100BaseT (X) Auto   |
| Transmission Mode                     | Store and Forward(full wirespeed)  |
| Bandwidth                             |  |
| Packet Forwarding                     | 0.72Mpps   |
| MAC                                   | 1K   |
| Buffer                                | 768K   |
| Transmission Distance                 | 10BASE-T : Cat3,4,5 UTP(≤250 meter)<br>100BASE-TX : Cat5 or later UTP(150 meter) |
| Watt                                  | Standby Power Consumption: ≤3W;  |
| LED Indicator                         | PWR:Power LED<br>1-5:(Link LED=10/100MLink)                                      |
| Power                                 | External Power DC: 12V 0.5A  |
| Operating Temperature/Humidity        | -10~+55°C; 5%~90% RH Non coagulation   |
| Storage Temperature/Humidity          | -40~+75°C; 5%~95% RH Non coagulation   |
| Lightning Protection Level            | 6KV 8/20us; 8KV ESD<br>IP40  |
| Product Size/<br>Packing Size (L*W*H) | 88mm*83mm*25mm<br>105mm*105mm*63mm   |
| N.W/G.W(kg)                           | 0.2kg/0.3kg  |
| Installation                          | Desktop  |
| Certificate                           | 3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;              |
| Warranty                              | Whole device for 1 year(Accessories not included)                                |

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.