

【S5800-16G-2S】
PARAMETER



Front



Back

Model	S5800-16G-2S
Product	Enterprise all Gigabit 16+2 Ethernet Switch
Fixed Port	16*10/100/1000Base-TX RJ45 port (Data) 2*1000M SFP
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u100BASE-TX IEEE 802.3ab1000BASE-T IEEE 802.3z 1000BASE-X IEEE 802.3x IEEE 802.1q VLAN
Function	N_Standard normal; V_Port isolation; C_Flow Control mode
Port Specification	10/100/1000BaseT （X） Auto
Transmission Mode	Store and Forward （full wirespeed）
Bandwidth	56Gbps
Packet Forwarding	40.32Mpps
MAC Address	8K
Buffer	4.1M
Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(150 meter) 1000BASE-SX: 62.5μm/50μm MMF(2m~550m) 1000BASE-LX: 62.5μm/50μm MM(2m~550m) or 10μm SMF(2m~5000m)
Watt	≤20W
LED Indicator	PWR:Power LED 1-16:(Link LED =10/100/1000M) 17-18:(Gigabit uplink LED)
Power	Built-in Power AC： 100～240V 50-60Hz 1A
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product size/Packing size （L*W*H）	440mm*200mm*45mm 513mm*300mm*95mm
N.W/G.W （kg）	1.6kg/2.2kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning protection level	3KV 8/20us； IP30
Certificate	3C； CE mark, commercial； CE/LVD EN60950； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)