

Model	S5800-48G-2S
Product name	Full Gigabit 48+2 Ethernet Switch
Fixed Port	48*10/100/1000M RJ45 port 2*1000M SFP
Bandwidth	128Gbps
Packet Forwarding	74.40Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10 Mbps: Cat3,4,5 UTP (≦ 250 meters) 100 Mbps: Cat5 or later UTP (150 meters) 1000 Mbps: Cat6 or later UTP (150 meters) SFP: Supports 1000M single-mode multi-mode optical modules, with a maximum distance of ≦ 120km (depending on the optical module)
LED Indicator	PW: Power indicator light 1-48: PoE working indicator light 49-50: SFP optical port connection indicator light
Power	Built-in Power AC: 100~240Vac 50-60Hz 0.5A
Watt	Standby Power Consumption: ≦30W
Operating Temperature /Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	440mm*230mm*45mm 515mm*375mm*95mm
N.W/G.W (kg)	2.8kg/3.7kg
Installation	Rack-mount(optional machine hanger spare parts)
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.