

【S5800-48G】
PARAMETER



Front



Back

Model	S5800-48G
Product	Enterprise all Gigabit 48 ports Ethernet Switch
Fixed Port	48*10/100/1000Base-TX RJ45 port (Data)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u100BASE-TX IEEE 802.3ab1000BASE-T
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward (full wirespeed)
Bandwidth	112Gbps
Packet Forwarding	80.64Mpps
MAC Address	8K
Buffer	4.1M
Transmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(150 meter)
Watt	≤45W
LED Indicator	PWR:Power LED 1-48:(Link LED =10/100/1000M)
Power	Built-in Power AC: 100~240V 50-60Hz 1A
Operating Temperature/Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	440mm*200mm*45mm 513mm*300mm*95mm
N.W/G.W (kg)	2.2kg/3.5kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning protection level	3KV 8/20us; IP30
Certificate	3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)