

Model	S800-24F
Product name	24 Port Fast Ethernet Switch
Fixed Port	24*10/100Base-TX RJ45 port(Data)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.1q
Port Specification	10/100BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	4.8Gbps
Packet Forwarding	3.45Mpps
MAC	2K
Buffer	1.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter)
Watt	Standby Power Consumption: ≤10W;
LED Indicator	PWR:Power LED 1-24:(Link LED=10/100M Link)
Power	Built-in Power AC: 100~240V 50-60Hz 1A
Operating Temperature/Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃; 5%~95% RH Non coagulation
Lightning Protection Level	3KV 8/20us; IP30
Product Size/ Packing Size (L*W*H)	305mm*140mm*45mm 410mm*275mm*95mm
N.W/G.W(kg)	1.6kg/2.1kg
Installation	Desktop
Certificate	3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.