

Model	S800-24G
Product name	24 Port Gigabit Ethernet Switch
Fixed Port	24*10/100/1000Base-TX RJ45 port (Data)
Network protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x IEEE 802.1q VLAN
Port Specification	1-24 *10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	56Gbps
Packet Forwarding	40.32Mpps Supports 9K jumbo frame transmission
MAC	8K
Buffer	4.1M
Function	N:(standard normal)V:(port isolation)C:(Flow Control mode)
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≦250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
LED Indicator	Power LED 1-24: (Link LED=10/100M Link、1000M=Gigabit Link)
Power	Built-in Power AC: 100~240V 50-60Hz 1A
Watt	Standby Power Consumption: ≦20W
Operating Temperature /Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	305mm*140mm*45mm 410mm*275mm*95mm
N.W/G.W (kg)	1.6kg/2.1kg
Installation	Desktop
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.