

【S800-8G】
PARAMETER



Front



Back

Model	S800-8G
Product	All Gigabit 8 Ports Ethernet Switch
Fixed Port	8↑10/100/1000M Base-TX RJ45 (Data)
Network Protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T
Port Specification	10/100/1000BaseT (X) Auto
Transmission Mode	Store and Forward (full wirespeed)
Bandwidth	16Gbps
Packet Forwarding	11.52Mpps
MAC Address	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
Watt	≤6W
LED Indicator	PWR:Power LED Port:(Green=10/100M LED+Orange=1000M LED)
Power	External Power DC: 12V 0.5A
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product size/Packing size (L*W*H)	175mm*75mm*28mm 215mm*175mm*45mm
N.W/G.W (kg)	0.4kg/0.6kg
Installation	Desktop
Lightning protection level	3KV 8/20us; IP30
Certificate	CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)