

|                       |  |
|-----------------------|--|
| Model                 | F1100W-6SX-2XGT-SE   |
| Product name          | Full 10 Gigabit Fiber Optic WEB Managed Switch   |
| Fixed Port            | 2*100M/1G/2.5G/5G/10G Base-TX uplinks RJ45 ports<br>6*1G/2.5G/10G SFP+   |
| Console Port          | 1  |
| RET hole              | 1  |
| CPU                   | MIPS-34Kc 800MHz   |
| DDR                   | 2G DDR3  |
| Flash                 | 256MBytes  |
| Bandwidth             | 160Gbps  |
| Packet Forwarding     | 119.04Mpps   |
| MAC                   | 16K  |
| Buffer                | 12 Mbit SRAM packet buffer   |
| Jumbo frames          | 12Kbyte  |
| Transmission Distance | 100BASE-TX : CAT 5 and up UTP (≤150m)<br>2.5G/1G BASE-TX: CAT 6 and up UTP(≤150m)<br>5G BASE-TX: CAT 6 and up UTP (≤100m)<br>10G BASE-TX: CAT 6 and up UTP (≤50m)<br>SFP: Support 1G/2.5G/10G single-mode and multi-mode optical modules, maximum distance ≤ 120km (depending on the optical module) |
| LED indicator light   | PWR: Power LED/System LED<br>1-8 Ports: Link/Act LED (green)<br>10G Status LED (red)   |
| power supply          | DC 12V 2.5A MAX 24W  |
| Usage Environment     | Operating temperature: -10 ~ 55°C;<br>Storage temperature: -40 ~ 75°C;<br>Operating humidity: 5% ~ 90% RH Non-condensing<br>Storage humidity: 5% ~ 95% RH Non-condensing   |
| Product Size(L*W*H)   | Product size: 223mm*112mm*31mm<br>Package size: 270mm*220mm*65mm   |
| N.W(kg)               | 0.83kg/1.12kg  |
| Installation          | desktop  |
| Warranty              | Whole device for 1 year(Accessories not included)  |

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.