

<div><div>hasivo®</div><div>Hardware specifications</div></div>	
Model	F1100W-4SX-4XGT
Product name	Full 10 Gigabit Fiber Optic L3 Managed Switch
Fixed Port	4*100M/1G/2.5G/5G/10G Base-TX uplinks RJ45 ports 4*1G/2.5G/10G SFP+
PoE Port	Port 5: IEEE802.3af/at/bt MAX 90W Port 6-8: IEEE802.3af/at MAX 30W1
PoE Power	MAX 120W
Console Port	1
RET hole	1
CPU	MIPS-34Kc 800MHz
DDR	2G DDR3
Flash	256MBytes
Bandwidth	160Gbps
Packet Forwarding	119.04Mpps
MAC	16K
Buffer	12 Mbit SRAM packet buffer
Jumbo frames	12Kbyte
Transmission Distance	100BASE-TX : CAT 5 and up UTP (≦150m) 2.5G/1G BASE-TX: CAT 6 and up UTP(≦150m) 5G BASE-TX: CAT 6 and up UTP (≦100m) 10G BASE-TX: CAT 6 and up UTP (≦50m) SFP: Support 1G/2.5G/10G single-mode and multi-mode optical modules, maximum distance ≦ 120km (depending on the optical module)
LED indicator light	PWR: Power LED/System LED 1-8 : Link/Act LED (green)    10G Status LED (red) PoE 5-8 ports: PoE LED
power supply	DC 52V 2.5A
Usage Environment	Operating temperature: -10 ~ 55°C; Storage temperature: -40 ~ 75°C; Operating humidity: 5% ~ 90% RH Non-condensing Storage humidity: 5% ~ 95% RH Non-condensing
Product Size(L*W*H)	Product size: 223mm*112mm*31mm Package size: 270mm*220mm*65mm
N.W(kg)	0.93kg/1.22kg
Installation	desktop
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.