hasivo®

硬件规格

	Model	FS-PSE90W-UP
	Product name	Gigabit IP67 outdoor waterproof booster PSE injoctor
	Material	Aluminum die-casting body Nylon waterproof joint
	Waterproof grade	IP67
	Wire diameter	Support network cables with a Φ of 4-8mm
	Fixed Port	1*10/100/1000/2500BASE-TX in 1*10/100/1000/2500BASE-TX out
	DC in	89-96%(DC12-57) MAX 140W 2P*3.5mm connection terminal
	PoE in Pin	12+ 45+ 36- 78-
	PoE OUT	Supports IEEE802.3af/at/bt, max 90W PoE out
	PoE OUT Pin	Bt:12+ 45+ 36- 78- Af/at: 12+ 36-
Tran	POE out nsmission Distance	10BASE-T: Cat3,4,5 UTP(≤250 meter) 100BASE-TX: Cat5 or later UTP(150 meter) 1000BASE-TX: Cat6 or later UTP(100 meter) 2500BASE-TX: Cat6 or later UTP(100 meter)
	LED Indicator	PW: Power in led 48V: Input voltage is normal Af/at: Port af/at PoE out ON Bt: Port Bt PoE out ON
	Operating Temp- erature/Humidity	-40~+80°C; 5%~90% RH Non coagulation
	Storage Temp- erature/Humidity	-40~+90°C; 5%~95% RH Non coagulation
	roduct/Packing size (L*W*H)	150*77*43mm 160*85*47mm
	N.W/G.W (kg)	0.27kg/0.31kg
F	Lightning Protection level	6KV 8/20us;
	Installation	Desktop、wall installation
	Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
	Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.