

Model	S1100W-8GT-1SX-S
Product name	10G Uplink Smart WEB Managed Switch
Fixed Port	8*10/100/1000/2500Base-TX uplink RJ45 port (Data) 1*1000/2.5G/10G SFP+ (Data)
Jumbo Frame	12Kbyte
Bandwidth	60Gbps
Packet Forwarding	49.76Mpps
MAC	4K
Buffer	8.1 Mbit SRAM Packet Buffer
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(≤150 meter) 1000BASE-TX：Cat6 or later UTP(≤150 meter) 2500BASE-TX：Cat6 or later UTP(≤100 meter)
LED Indicator	PWR:Power LED/SYS LED 1-8 Ports: Link/Act LED、1G speed LED、2.5G speed LED Port 9: Link/Act LED
Power	External power DC：12V1.5A max 13W (100-240Vac 50/60Hz 0.2A)
Operating Temperature /Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃；5%~95% RH Non coagulation
size	Product :175mm*70mm*28mm Packing:197mm*170mm*40mm
N.W/G.W (kg)	0.33kg/0.53kg
Installation	Desktop
Certificate	3C；CE-EMC EN55032；CE-LVD EN62368；FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.