

Model	S1100WP-8GT-2S+
Product name	10G Fiber uplink+2.5GE LAN Managed PoE Switch
Fixed Port	8*100/1000/25000 Base-TX PoE port (Data/Power) 2*1000/250010000M SFP
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W/port PoE out 2-8 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	max 120W
DDR	2G DDR3
buffer	Integrated 1.5MB packet buffer
FLASH	256MBytes
RAM	256MBytes
Bandwidth	80Gbps
Packet Forwarding	59.52Mpps
MAC	16K
Buffer	12 Mbit SRAM Packet Buffer
Jumbo Frame	Jumbo frame up to 12KB
VLAN Address	4K
Twisted pair transmission	100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) 2500BASE-TX : Cat6 or later UTP(100 meter) SFP: 100M/1G/2.5G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED indicator light	PWR:Power LED(sys led) Port:Network connection indicator Port1-8: Link/Atc 2.5G Speed LED Port9-10: 1G.2/5G Link/ACT 10G Link/Act
Power	External power DC: 12V 2A max 15W (100-240Vac 50/60Hz 0.4A)
Operating Temperature/Humidity	-20~+55°C; 10%~90% RH No coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH No coagulation
Product Size(L*W*H)	230mm*115mm*33mm 260mm*220mm*68mm
N.W(kg)	0.74kg/1.02kg
Installation	Desktop
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.