

Model	S5800W-48G-4SX-SE
Product name	48-port GigabitSmart WEB switch
Fixed Port	48*10/100/1000Mbps RJ45 Port 4*10G SFP+
Reset Key	1
Bandwidth	256Gbps
Packet Forwarding performance	92.32Mpps store and forward
network standards	IEEE802.3、IEEE802.3u、IEEE802.3U、IEEE802.3ab、IEEE802.3Z、IEEE802.3x
Transmission Distance	10BASE-T:3- 4-5 unshielded twisted pair cables (<250m) 100BASE-T: Category 5 and above unshielded twisted pair cables (<150m) 1000BASE-T: Category 6 and above unshielded twisted pair cable (≤ 150m) SFP: Supports 1G/2.5G/10G single-mode multi-mode optical modules, with a maximum distance of ≤ 120km (depending on the optical module)
LED Indicator	PW: Power indicator light SYS: System indicator light 1-48:link/ACT 49-52-10G: Speed indicator light 49-52-GIGA: Speed indicator light
Input power supply	≤30W
Usage environment	Working temperature: -10 °C~55 °C Storage temperature: -40 °C~75 °C Working humidity: 10% to 90%, non solidifying Storage humidity: 5% to 90%, non solidifying
size	Product size: 440 * 360 * 45mm Packaging size: 553 * 403 * 93mm
N.W/G.W (kg)	5.61/6.46kg
Installation	Desktop/rack mounted
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.