

hasivo® Hardware specifications	
Model	G2600W-16G-4S
Product name	Industrial 4+16 Full Gigabit Managed Switch
Fixed Port	16*10/100/1000Base TX RJ45 ports (Data) 4*1000M optical ports
Management port	1*console port
Reset key	1
Network protocol	IEEE 802.3x IEEE 802.3、IEEE 802.3u、IEEE 802.3ab、IEEE 802.3z IEEE 802.3ad IEEE 802.3q 、IEEE 802.3q/p IEEE 802.1w、IEEE 802.1d 、IEEE 802.1S IEEE 802.3z 1000BASE-X STP(Spanning Tree Protocol) RSTP/MSTP(Rapid Spanning Tree Protocol) EPPS ring network protocol EAPS ring network protocol
Port characteristics	10/100/1000BaseT （X） Automatic detection， full/half duplex MDI/MDI-X adaptive
Bandwidth	56Gbps （No blocking）
Packet Forwarding	41.664Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(=250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximumdistance =120km (depending on the optical module)
FLASH	16M
RAM	128M
No-load power consumption	≤3W
Forwarding mode	Store and forward (full line speed)
LED Indicator	V1:Mains power indicator V2:Secondary power indicator 1-16 Port RJ45 left: 1000M link LED (orange) RJ45 right: Link LED (green) 17-20: optical port link LED
Supporting power supply	Built in AC： 100~240V 50/60HZ
Storage Temperature/ Humidity	-40~+80°C;10%~90% RH No coagulation
Operating Temperature/ Humidity	-40~+85°C;5%~95% RHR No coagulation
Product size/Packing size(L*W*H)	207mm*141mm*50mm 280mm*166mm*79mm
N.W/G.W(kg)	1.54kg/1.71kg
Installation	DIN rail type (another wall mounting lug)
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.