

Model	S1300WP-8XGT-2XGT-2S+
Product name	Full 10G 12-port WEB Management PoE Switch
Fixed Port	10*10G/5G/2.5G/1G/100M RJ45 port 2*10Gbps SFP+ port
PoE Port	1 port supports IEEE802.3af/at/bt, Max 90W 2-8 port supports IEEE802.3af/at, Max 30W
PoE Power	MAX 240W
Console Port	1
RET hole	1
CPU	MIPS InterAptiv, Dual Core 1GHz
DDR	4G DDR3
RAM	512M
Bandwidth	240Gbps
Packet Forwarding	178.56Mpps
MAC	32K
Buffer	16M
Jumbo frames	Supports up to 12KB
Transmission Distance	100BASE-T: Cat5 or later UTP(\leq 150m) 1000BASE-T: Cat6 or later UTP(\leq 150m) 2500BASE-T: Cat6 or later UTP(\leq 100m) 5000BASE-T: Cat6 or later UTP(\leq 80m) 10000BASE-T: Cat6 or later UTP(\leq 30m) SFP+: Supports 10G single-mode multimode optical modules with a maximum distance of \leq 120km (depending on the optical module)
LED indicator light	SYS:System indicator POE:POE LED 10G RJ45 Left: 10G link LED (orange) / 2.5G link LED (green) Right: link LED (green) 11-12: 10G Link LED/Link LED
Power	100-240Vac 50/60Hz 3.6A Max 300W
Usage Environment	Operating temperature: -10 ~ 55°C; Storage temperature: -40 ~ 75°C; Operating humidity: 5% ~ 90% RH Non-condensing Storage humidity: 5% ~ 95% RH Non-condensing
Product Size(L*W*H)	Product Size: 440mm*290mm*45mm Package Size: 515mm*375mm*95mm
N.W(kg)	2.82kg/3.62kg
Installation	Desktop/rackmount
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.