

Model	S1300W-4XGT-8S+
Product	Full 10G L3 Managed Switch
Fixed Port	4*100/1000/2500/5000/10000Mbps RJ45 port 8*1/2.5/10Gbps SFP+ Optical Port
Console port	1*console port
Reset Key	1
CPU	MIPS InterAptiv, Dual Core 1GHz
DDR	4G DDR3
FLASH	512MBytes
RAM	64M
Bandwidth	240Gbps
Packet Forwarding	178.56Mpps
MAC	32K
Buffer	16M
Jumbo Frame	Jumbo frame up to 12KB
Transmission Distance	100Mbps : Cat5 or later UTP(≤150 m) 1000Mbps : Cat6 or later UTP(≤150 m) 2500Mbps : Cat6 or later UTP(≤100 m) 5000Mbps: Cat6 or later UTP(≤80 m) 10000Mbps: Cat6 or later UTP(≤30 m) SFP+: Supports 10G single-mode multimode optical modules with a maximum distance of ≤120km (depending on the optical module).
LED Indicator	SYS:System indicator 1-8: 10G Link LED/Link LED 10G RJ45 Left: 10G link LED (orange) / 2.5G link LED (green) Right: link LED (green)
Power	100-240Vac 50/60Hz 0.3A
Use environment	Operating temperature: -10°C~55°C Storage temperature: -40°C~75°C Operating humidity: 5%~90% RH Non coagulation Storage humidity: 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	Product Size: 440mm*290mm*45mm Package Size: 515mm*375mm*95mm
N.W/G.W(kg)	2.82kg/3.62kg
Lightning Protection level	6KV 8/20us; IP30
Installation	Desktop/rackmount
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.