



# KEPERSURF®-389 Surface control additive

# KEPERSURF® -389

# Acrylic levelling agent for water-based systems

## Product type

Ionic-type acrylate copolymer levelling agent

#### Product usage

Reduce the surface tension in the water-soluble system, improve the floating and levelling, it can effectively solve the defects such as shrinkage hole and orange peel, good wetting ability for substrate and pigments.

#### Physical data

- 1. Effective ingredient: ionic-type acrylate copolymer
- 2.Appearance: colorless-light yellow transparent liquid
- 3. Content: 35±2%
- 4.Specific gravity: about1.02(25°C)
- 5.Solvent: DPM/water

## Product features

- 1.Effectively improve the fluidity and spreadability of paint solution, improve the gloss of the system.
- 2. Excellent anti-shrinkage hole ability, improve the appearance of paint film, reduce orange peel, fish eye and other defects.excellent leveling performance.
- 3.It has the inhibiting foam effect and improving the debubbling property of paint film.
- 4. Effectively reduce the surface tension of the system, improve the wettability of substrate and pigments, and help the pigment disperse.
- 5.No adverse effect to adhesion, can be used for baking paints.

#### Suggested dosage

According to the supply type, For the total amount of formula: 0.1-1% The best dosage needs to be obtained through testing

# Add methods and precautions

- 1.Can be diluted with water or common solvents
- 2.Ensure that the useing system remains alkaline

3.Can be added at any stage of coating manufacturing, but ensure that it is evenly dispersed in the coating system

## Scope of application

珠海市金团化学品有限公司

KITO CHEMICAL CO., LTD

Suitable for water-based industrial coatings and inks, can be used for baking paints.

Tel:+0086-760-88819466 Fax:+0086-760-88818561 Add:No. 80,Nanhua Fifth Road, Nanshui Town,Jinwan District, Zhuhai City,Guangdong Chian Http:www.kitochem.com

# TDS



# KEPERSURF<sup>®</sup>-389 Surface control additive

# Safety instructions

Refer to the MSDS

# Packing specifications

- 1. Product:25KG,180 KG plastic bucket
- 2. Sample:60ml glass bottle

## Transportation and storage

- $1\,{\rm v}$  Containers should be sealed during transport and storage, and no freezing and ambient temperature lower than  $40^{\circ}{\rm C}$  .
- 2. The shelf life is 2 years, starting from the date of production.

The content of this information is based on our current knowledge and experiments, Since we cannot test the nature of this product, especially mixed products from other suppliers, therefore, we remind you that prior to formal use, you should test your performance to meet your requirements. We reserve the right to make technical improvements and changes to this product, and all the information contained in this information is not in the nature of any legal guarantee.

珠海市金团化学品有限公司 KITO CHEMICAL CO., LTD. Tel:+0086-760-88819466 Fax:+0086-760-88818561 Add:No. 80,Nanhua Fifth Road, Nanshui Town,Jinwan District, Zhuhai City,Guangdong Chian Http:www.kitochem.com