TDS



KEPERDISP[®]-958 Adhesion additive

KEPERADH® -958

PP adhesion agent

Product type

Chlorinated polyolefin

Product usage

As adhesion additives in a variety of coating formulations

Physical data

1. Effective ingredient: chlorinated polyolefin

2. Appearance: slightly yellow, transparent liquid

3. Content: 20±2%

4. Specific gravity: about 0. 91(25°C)

5.Solvent: Xylene / butyl acetate

Product features

1.Excellent adhesion to PP, EPDM substrate and common PU surface paint.

2.It can be used as an adhesive to bind aluminum foil powder, nitrocellulose cellophane, polyester and other plastics.

Suggested dosage

1.PP primer: use toluene and xylene to dilute into 2-3% non-volatile solution, directly spray, film thickness 2-7 microns . flash drv for 10 minutes after spraving top paint 2. PP adhesion additives: added directly to the primer or top coat according to the formula (about 10-20%).

The best dosage, drying temperature and drying time should be obtained through testing

Add methods and precautions

1.Can be added at any stage of paint manufacturing, added slowly

2. When dispersing, there should be a certain shear force to ensure that it is evenly dispersed in the coating system

Scope of application

Suitable for solvent type PP / EPDM primer, background color paint

Safety Instructions

Refer to the MSDS

Packing specifications

- 1、25KG,180 KG iron bucket
- 2、Sample:60ml glass bottle

TDS



KEPERDISP[®]-958 Adhesion additive

Transportation and storage

- 1. Containers should be sealed during transport and storage, and no freezing and ambient temperature lower than $40^{\circ}{\rm C}$.
 - $2\sqrt{10}$ The shelf life is 2 years, starting from the date of production.

The content of this information is based on our current knowledge and experiments, Since we cannot test the nature of this product, especially mixed products from other suppliers, therefore, we remind you that prior to formal use, you should test your performance to meet your requirements. We reserve the right to make technical improvements and changes to this product, and all the information contained in this information is not in the nature of any legal guarantee.