



Size:60*60*20mm

General Specifications:

Motor: 4 pole brushless DC motor

Frame: Thermoplastic PBT+30%GF

Impeller: Thermoplastic PBT+15%GF

Bearing: Precision Ball Bearing/Sleeve Bearing

Storage temperature: -40℃ to +75℃

Operating temperature:-10℃ to +70℃




Major Characteristic Parameters



MODEL	Bearing System	Rated Voltage (V)	Rated Current (A)	Input Power (W)	Speed (RPM)	Max Air Flow (CFM)	Max Static Pressure (mm H2O)	Noise (dBA)	Weight (g)
FD1260207S(B)	S/B	12	0.20	2.40	4500	20.22	5.56	34.0	55
FD1260205S(B)	S/B	12	0.15	1.80	4000	19.55	4.46	32.0	55
FD1260203S(B)	S/B	12	0.12	1.44	3500	16.99	3.48	28.0	55
FD1260201S(B)	S/B	12	0.10	1.20	3000	14.08	2.58	25.0	55
FD2460207S(B)	S/B	24	0.14	3.36	4500	20.22	5.56	34.0	55
FD2460205S(B)	S/B	24	0.11	2.64	4000	19.55	4.46	32.0	55
FD2460203S(B)	S/B	24	0.08	1.92	3500	16.99	3.48	28.0	55
FD2460201S(B)	S/B	24	0.05	1.20	3000	14.08	2.58	25.0	55

* B: Two Ball bearing S: Sleeve Bearing * All reading are typical values at rated voltage

* Function type optional * Specifications are subject to change without notice



Characteristic Curve

