



**Size: 60\*60\*38mm**

**General Specifications:**

- Motor: 4 pole brushless DC motor
- Frame: Thermoplastic PBT+30%GF
- Impeller: Thermoplastic PBT+15%GF
- Bearing: Precision Ball Bearing/Sleeve Bearing
- Storage temperature: -40°C to +75°C
- Operating temperature: -10°C to +70°C



**Major Characteristic Parameters**



Model 型号	Bearing Type 轴承类型	Rated Voltage 额定电压 VDC	Current 电流 A	Speed 转速 RPM	AirFlow 风量 CFM	Pressure 风压 mmH <sub>2</sub> O	Noise 噪音 dBA	Weight 重量 g
FD2460389S/B	Sleeve/Ball	24	0.5	10000	49.83	21.3	57	106
FD2460387S/B			0.37	9000	43.51	16.4	53.9	
FD2460385S/B			0.3	8000	36.72	12.5	49.3	
FD2460383S/B			0.2	7000	30.58	8.77	44.4	
FD1260389S/B	Sleeve/Ball	12	1	10000	49.83	21.3	57	
FD1260387S/B			0.65	9000	43.51	16.4	53.9	
FD1260385S/B			0.6	8000	36.72	12.5	49.3	
FD1260383S/B			0.4	7000	30.58	8.77	44.4	

\* B: Two Ball bearing S: Sleeve Bearing \* All reading are typical values at rated voltage  
 \* Function type optional \* Specifications are subject to change without notice

