



Size:80*80*25 mm

General Specifications:

- Die-cast aluminum housing
- Metal impeller or Class fiber reinforced plastic:
Impeller are UL 94V-0 rating
- Shaded pole motor
- Impedance protected
- Bearing: Precision Ball Bearing/Sleeve Bearing
- Storage temperature: -40℃ to +75℃
- Operating temperature:-10℃ to +70℃



Specifications

Model 型号	Bearing System 轴承	Rated Voltage (V) 电压	Freq. (Hz) 频率	Current (A) 电流	Input Power (W) 功率	Speed (RPM) 转速	Air Flow (CFM) 风量	Static Pressure (mm-H ₂ O) 静压	Noise Level (dB-A) 噪音	Weight (g) 重量
8025HS/B1	Sleeve/Ball	110	50/60	0.13/0.11	17.0/15.0	2600/3000	21/24	4.0/5.5	28.2/33	240
8025MS/B1		110	50/60	0.11/0.10	13.0/10.0	2300/2600	18/21	2.9/3.4	28.2/33	
8025HS/B2		220	50/60	0.09/0.08	17.0/15.0	2600/3000	21/24	4.0/5.5	28.2/33	
8025MS/B2		220	50/60	0.06/0.05	13.0/10.0	2300/2600	18/21	2.9/3.4	28.2/33	

* B: Two Ball bearing S: Sleeve Bearing * All reading are typical values at rated voltage

* Function type optional * Specifications are subject to change without notice

