



Size:120*120*32mm

General Specifications:

Motor: 4 pole brushless DC motor

Frame: Thermoplastic PBT+30%GF

Impeller: Thermoplastic PBT+15%GF

Bearing: Precision Ball Bearing/Sleeve Bearing

Storage temperature: -40℃ to +75℃

Operating temperature:-10℃ to +70℃



Major Characteristic Parameters



Model 型号	Bearing Type 轴承类型	Rated Voltage 额定电压	Current 电流	Speed 转速	Air Flow 风量	Pressure 风压	Noise 噪音	Weight 重量
		VDC	A	RPM	CFM	mmH ₂ O	dBA	g
BD2412329S/B	S/B	24	0.50	2800	42.45	41.10	61.3	240
BD2412327S/B			0.35	2400	36.38	30.26	52.4	
BD2412325S/B			0.20	2100	31.83	25.10	45.8	
BD2412323S/B			0.12	1700	25.40	16.21	38.3	
BD1212329S/B		12	0.80	2800	42.45	41.10	61.3	
BD1212327S/B			0.60	2400	36.38	30.26	52.4	
BD1212325S/B			0.35	2100	31.83	25.10	45.8	
BD1212323S/B			0.25	1700	25.40	16.21	38.3	

* B: Two Ball bearing S: Sleeve Bearing * All reading are typical values at rated voltage

* Function type optional * Specifications are subject to change without notice

