PROJECT PRODUCTS

Drywall Metal framing

Advantages

Drywall metal framing is the process of constructing a metal or wood frame to which drywall sheets are attached to create interior walls and ceilings. Unlike traditional lath and plaster techniques, Metal drywall framing offers a faster, more cost-effective method for dividing spaces and creating smooth surfaces. The frame provides the structural support needed for the drywall panels, ensuring they are securely fixed and properly aligned.





Application

With the advancement of China's modernization, light steel keel has found widespread application in hotels, terminals, bus stations, train stations, amusement parks, shopping malls, factories, office buildings, old building renovations, interior decoration settings and ceilings.



Installation Node Diagram













SHAANKI ENZEDE CORATION MATERIALS CO., LTD 1/02

陕西恩泽装饰材料有限公司 SHAANXI ENZEDECORATION MATERIALS CO., LTD SHAANXI ENZEDE CORATION MATERIALS CO., LTD 陕西恩泽装饰材料有限公司


PROJECT PRODUCTS

Furring Channel Ceiling System









Furring channel

 $35 \times 22 \times 68$ mm $\times 3000$ mm $32 \times 22 \times 68$ mm $\times 3000$ mm $35 \times 17 \times 62$ mm $\times 3000$ mm

Thickness

0.40, 0.45, 0.50mm





Main channel

 $38 \times 10 \times 3000$ mm $38 \times 12 \times 3000$ mm

Thickness:

0.40, 0.45, 0.50mm





Wall angle


 $25 \times 25 \text{mm} \times 3000 \text{mm}$ 24×24 mm $\times 3000$ mm Thickness:

0. 40, 0. 45, 0. 50mm

Accessories

PROJECT PRODUCTS

CD/UD Ceiling System











0.3mm, 0.35mm to 0.60mm



UD Profile $27 \times 28 \times 3000$ mm $27 \times 28 \times 2800$ mm



0.3mm, 0.35mm to 0.60mm



U clamp



Double hanger

Cross Connector

Adjustable Hanger

CD connector