




Professional commercial radio solutions

ETMY ET-300C

ET-300C has an exquisite and dexterous appearance and a comfortable grip. In terms of voice quality design, it adopts a sustainable and reasonable cavity space and has a better voice effect.

ET-300C guarantees a variety of communication needs with superior quality, and is a value choice for users in construction, property, industry, etc.



Parameters

Functions

- FM radio function
- Power Saving Function
- Priority scan
- Channel scan
- Time-out timer(TOT)
- CTCSS/DCS
- Busy channel lock(BCL)
- QT/DQT
- Scramble function
- Tail cancellation
- Channel companding

General

Frequency Range	VHF: 136 ~ 174 MHz / UHF: 403~470 MHz
Channel Spacing	25KHz / 12.5KHz
Channel Number	16
Antenna impedance	50 Ω
Operating temperature Range	-20°C~ +60°C
Operating Voltage	DC 7.4V ± 20%
Dimension	125 × 54 × 32 mm
Weight	208g (Including battery, antenna)
Battery	2000mAh lithium battery
Protection Grade	IP66


Transmission part

Output Power	1W / 5W
Modulation	16K0F3E
Signal to noise ratio	≤-40dB
Emission spurious	≤-36dBm
Harmonic power	≤65dB
Adjacent channel power	≥65dB
Audio response	300Hz-3KHz
Audio distortion	≤5%

Receiving part

Receiving sensitivity	-120dBm (20db SINAD)
Audio Power	1W
Intermodulation	≥60dB
Adjacent channel selectivity	≥60dB
False signal response	≥60dB
Audio response	300Hz-3KHz
Signal to noise ratio	≥45dB
Audio distortion	≤5%

Standard accessories



Scan for more of our products