



Professional commercial radio solutions

# ETMY ET-79

ET-79 is powerful and versatile and integrates the best function of two-way radio.

ET-79 provides higher excellent voice quality and long battery life.

This means you will be able to increase employees productivity and reduce operating costs.



## Specification

### General

Frequency Range	UHF: 400 ~ 480 MHz
Channel Number	16
Antenna Impedance	50 Ω
Operating Temperature Range	-20°C~ +50°C
Operating Voltage	DC 7.4V
Dimension	125x 60x 35 mm
Weight	211g (include battery, antenna)
Battery Capacity	2300mAh lithium battery


### Transmission part

Output Power	≤5W
Modulation	FM
Maximum Frequency Deviation	<±5 KHz
Residual Wave Radiation	< -60 dB
Pre-emphasis Feature	≤60dB
Radio Emission Current	≤1000mA
Audio Distortion	≤5%


### Reception part

Sensitivity	<0.16μV (12dB SINAD)
Audio Output Power	≥0,3W
Intermodulation	50 dB
Receive Current	≤100mA
Clutter Suppression	≥65dB

### Applicable scenes




Outdoor




Construction site



Security



Military



Marine COSCO

### Standard accessories



Back clip



Antenna



Battery



Charger



Sling



Manual



Scan for more of our products