



Scan for more of our products

# ET-D70

## DMR Digital Portable radio



### Suitable occasions



- Digital/Analog Dual Mode
- 1024 channels
- TDMA dual slot
- 32 scan lists, 16 areas
- Digital encryption
- 800 contacts
- Digital alarm
- Recording function (optional)



## Specification

### General

Frequency Range	VHF: 136~174MHz / UHF: 400~480MHz
Channel Number	1024
Operating Voltage	DC 7.4V
Channel Spacing	25KHz / 12.5KHz
Operating Temperature range	-30°C~ +60°C
Frequency Stability	±0.5ppm
Dimension	123 × 63 × 39 mm (Not include the antenna)
Weight	≤280g (Include battery, antenna)
Battery	2500 mAh lithium battery
Antenna Impedance	50 Ω

### Transmission part

Output Power	VHF:1W / 5W;UHF: 1W / 4W
Modulation	25KHZ:16KφF3E / 12.5KHZ:11KφF3E
4FSK Digital modulation	12.5KHZ data: 7K60FXD 12.5KHZ voice and data: 7K60FXW
Digital Vocoder Type	AMBE++
Modulation Limit	≤+2.5kHz@12.5kHz
Stray Radiation	-36dBm<1GHz / -30dBm@1GHz
Hum and noise	≥-40dB @ 12.5KHz / ≥-45dB @ 25KHz
Audio Distortion	≤5%
Audio Response	300-3KHz, + 1/-3dB
Digital Protocol	ETSI-TS102 361 -1,-2, -3

### Receiving part

Analog sensitivity	≤-121dBm@12dB SINAD
Digital sensitivity	≤-119dBm@ 5%BER
Audio Power	> 1W
Intermodulation	≥-65dB @ 12.5KHz / 25KHz
Hum and noise	≥-40dB @ 12.5KHz/ ≥-45dB @ 25KHz
Adjacent Channel selectivity	≥60dB @ 12.5KHz/ <70dB @ 26KHz
Stray radiation	< -57dBm

### Standard accessories

