



Portable Two Way Radio

SMP 418

Compact Design & Loud Speaker

- RF TX Power: 4W
- Audio Output Power: 1W
- VOX / iVOX
- PC programmable
- Clone
- Frequency Range
 - UHF 330 ~ 400MHz
 - UHF 400 ~ 470MHz
 - UHF 435 ~ 480MHz
 - VHF 136 ~ 174MHz



Main Features

RF TX Power: $\leq 5W$
Metal Framework
Audio Output Power: 1W
Clone
VOX/iVOX

Other Features

9 Squelch Levels
Repeater Compatible
Programmable via PC
Monitor
Emergency Call
Busy Channel Lock

Accessory

1200mAh Li-ion Battery



Charger Base



Power Adapter



Belt Clip



Antenna



(For reference only)

Technical Specification

General Specification

SMP418

Frequency Range*	UHF 330 ~ 400MHz UHF 400 ~ 470MHz UHF 435 ~ 480MHz VHF 136 ~ 174MHz
Storage Channel	16
CTCSS/CDCSS	38/83
Channel Space	12.5KHz/25KHz
Operation Temp. Range	-25°C~+55°C
Dimension(H×W×T)	113×55×32mm
Weight(include battery and antenna)	232g
Power Supply	7.4V
Battery Life(5/5/90 duty cycle)	10hours

Receiver

Channel Spacing	12.5KHz/25KHz
Frequency Stability	$\pm 2.5PPm$
Audio Distortion	$\leq 5\%$


Transmitter


TX Power Output	$\leq 5W$
Channel Spacing	12.5KHz/25KHz
Frequency Stability	$\pm 2.5PPm$
Audio Output Power	$\leq 1000mW@8\Omega$
TX Power Switch	Yes

*Frequency Availability is limited by National laws and regulations.
Above specifications are all typical configuration values,
they may be subject to variations without notice

For more information, please visit website: www.smp.com.cn

Shanghai Motorola Telecom Products Co.,Ltd.

 is trademark of Shanghai Motorola Telecom Products Co., Ltd. Copyright Reserved.

 **MOTOROLA** is trademark of Motorola © Copyright 2010 Motorola Inc. All Rights Reserved