

JD-LED-029C



Die casting heatsink



Anti-glare board






Clear Injection
PC Diffuser



Opal PMMA
Diffuser



Die casting
Reflector



Application:



Walkways



Parks / Gardens



Car parks



Prestigious




Retail



Amenity

Distribution:



Features:

- Main body is made of Die-casting aluminum alloy with Extruded aluminum alloy.
- The diffuser is a clear anti-UV injection polycarbonate for high efficiency and vandal resistance.
- With anti-glare plate.
- Lumileds 2835/3030 led chip and Tridonic driver as regular ,Sosen,Meanwell,Osram,driver options.
- Easy access to LED and driver via a removable head.
- 2700-6500K color temperature options.
- Tamper proof fixings for increased vandal resistance.
- Anti-UV electrostatic powder spraying,regular color:Black,Silver,RAL7043,RAL7016.
- IP65 rating water and rust proof protection.
- IK08 rating housing protection.
- Warranty is 3-5 years.

Specification:

Item No.	LED	Lumens	Wattage	CCT	CRI
JD-LED-029-10W	Lumileds 2835	750Lm	10W	2700-6500K	≥80
JD-LED-029-14W	Lumileds 2835	1055Lm	14W	2700-6500K	≥80
JD-LED-029-20W	Lumileds 2835	1463Lm	20W	2700-6500K	≥80
JD-LED-029-24W	Lumileds 2835	1672Lm	24W	2700-6500K	≥80
JD-LED-029-30W	Lumileds 3030	2070Lm	30W	2700-6500K	≥80