


## ME-200-01/LED Flood Light



Size:

Unit (mm)



## ME-200-01/LED Flood Light



### Features:

1. The miniature / minimalist lamp body has the appearance design patent and conforms to the modern industrial aesthetics standard;
2. The whole structure adopts mechanical locking silicone pad technology to ensure high and low temperature durability;
3. It adopts exclusive ultra long-distance accurate projection technology and 93% transmittance ultra white tempered glass;
4. Adopt die-casting aluminum lamp body and composite metal high-efficiency heat conduction patented technology;
5. High efficiency DMX control system above 0.95 can be built in;
6. Semi buried installation.

### Parameter:

Lamp Parameter		LED parameter	
Beam Angle	20°30°45°60°	LED chip	Cree
case material/color	Die-casting aluminum(Black)	LED Item	XPL/XML
Cover material/color	Ultra clear tempered glass	CCT	Single color/RGBW
IP rate	IP66 structure waterproof	LED Power	10W
Lamp Power	18W-36W	Other Parameter	
Input Voltage	AC85-265V	Cable size	3 pins 1.5mm <sup>2</sup> rubber cable
PF	0.9	Cable length	300mm
Light Efficiency	85lm/w(white)	Fixing clip	Die-casting aluminum
Light angle	180°adjustable	Light distribution	
Cable location	From the bottom		
Control way	ON-OFF /DMX512		
Environment temperature	-30°C~+35°C		