

A	1		2		3		4							
	General technical parameters				Electrical technical parameters		Wiring Diagram							
	Stepping angle		1.8°		Rated voltage		24V DC							
	Number of phases		2		Rated current		4.4A (parallel)							
	Insulation resistance		100MΩMIN(500V DC)		Resistance		0.4±15%Ω							
	Insulation level		Class B/winding		Inductance		1.3±20% mH							
	Weight		About 1300g		Holding torque		1.4N.m							
B	Braking torque		400gf.cm REF.		Moment of inertia		About 330g.cm²							
	Overall dimension: unit=mm													
C	TOLERANCES (EXCEPT AS NOTES)		±0.3											
	MATERIAL		----						Y07-59D1-4008					
	FINISH		----											
			SYM		DATE		REVISION NO.		REVISIONS	BY	NOTE			
	DRAWN		DESIGNED		CHECKED		CHECKED		SCALE		1:1	TITLE	MOTR SPECIFICATION	THIRD ANGLI PROJECTION
	Dongguan Kaifull 19-01-04 Xu Yuanhao		Dongguan Kaifull 19-01-04 Xu Yuanhao									DWG.NO.	Y-19-0104-0	
									Guangdong Kaifull Electronics Technology Co., Ltd.		SHEET	1/1		