





Туре	Electric Linear Stage		
Stroke (mm)	100		
Lead (mm)	6		
Repeat positioning accuracy (µm)	±5		
Horizontal load (KG)	12		
Maximum thrust (N)	60		
Screw type	Ball Screw		
Screw grade	C5		
Motor model	Y07-35D47-4706 06GZ-178		
Step angle			
Number of phases	For specific		
Drive voltage	parameters, please		
Rated current	refer to the motor		
Resistance	specification		
Inductance	**		
Material	Aluminum alloy		
Surface treatment	Anodic color		
Main weight (kg)	1.0		
Motor Type	35 Open loop		
Sensor	built-in		

	-	5x25=125	-	
	29. 7 25	9-M4x0.7 <b>▼</b> 8		
	<b>9°</b>	+ +		R
22				
	67. 2	50	$+0.03$ $2-\emptyset 3 +0.01 \overline{\lor} 4$	

				YK-35D4706-06GZ-100-I			
				制图	叶振东	页	1/1
				审核		视角	$\oplus$
				检图		公差	未标注公差12级
序号	日期	更改内容	设计者	广东凯福电子科技有限公司			

Special Notes: (For internal production)

1. This model has a built-in sensor;

2. If the customer has no wiring requirements, the wiring will be in accordance with our company's standards