



Indoor Luminaire Photometric Data

Description Information

Luminary Name: 55252		Lum. Catalog:	Test ID:
Lamp Name:		Lamp Catalog:	Test Date: 2023/03/14
Manufacture:		Shld. Ang(°):	Test Machine:GON-2000
Test Lab:		Frequency (Hz):	Lamp CCT(K): 3000 Ra: 80
Lum. Size(W*L*H):0.050m*-0.050m*0.000m		Lum. Area(m2):0.002	Lum. W(kg): 0.000
Test System: C, γ	Test Step: C=30.0 γ=1.0	Temp.(°C): 25	Humidity(%):


Character Parameter

Lamp Speciality Parameter	Luminaire Speciality Parameter	
Rated Flux(lm): 625.090	Luminary Flux(lm): 625.090	Field Angle(10%Imax): 35.2(°)
Rated Power(W): 9	Luminary Efficiency: 100.00%	Down Lumens&Percent: 621.857lm 99.48%
Rated Voltage(V): 24	Luminary EER(lm/W): 67.672	Up Lumens&Percent: 3.233lm 0.52%
Tested Power(W): 9.237	Max. Candela(cd): 4624.529	S/MH: C0_a180=0.282 C90_270=0.281
Lamps' Inside: 1	Max Cand@Ang.(°): C=0.0 γ=0.0	CIE Type: Semi-Direct
Tested Electrics(V, A, pf):23.9, 0.386	Beam Angle(50%Imax): 16.4(°)	ErP Φ use(90°): 615.995lm
Lamp Size(W*L*H):0.050m*-0.050m*0.000m	Left=-8.5°, Right=7.9°	IRF(%): 1511.985



2D Plane Light Intensity Distribution Curve


Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14



3D Light Intensity Distribution Modal

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14

3D Light Intensity Distribution Modal



Curves:

View Angles:

3D Model

Orient:0

Fixture

Tilt:0

Vert. HUD

Roll:0

Hori. HUD

Spin:0

IES Indoor Report

Photometric Filename:UL-9W-COB-0900-BH-23度.IES

Zonal Flux Tabulation

Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (lm)	Sums Flux (lm)	Zone%Lamp	Sums%Lamp
0.0-1.0	4.40	4.40	0.70	0.70	47.0-48.0	0.77	617.53	0.12	98.79
1.0-2.0	12.92	17.32	2.07	2.77	48.0-49.0	0.67	618.21	0.11	98.90
2.0-3.0	20.63	37.94	3.30	6.07	49.0-50.0	0.58	618.78	0.09	98.99
3.0-4.0	27.14	65.08	4.34	10.41	50.0-51.0	0.49	619.27	0.08	99.07
4.0-5.0	32.15	97.23	5.14	15.56	51.0-52.0	0.42	619.70	0.07	99.14
5.0-6.0	35.46	132.70	5.67	21.23	52.0-53.0	0.37	620.06	0.06	99.20
6.0-7.0	36.99	169.69	5.92	27.15	53.0-54.0	0.32	620.38	0.05	99.25
7.0-8.0	36.86	206.55	5.90	33.04	54.0-55.0	0.28	620.66	0.04	99.29
8.0-9.0	35.36	241.92	5.66	38.70	55.0-56.0	0.24	620.90	0.04	99.33
9.0-10.0	32.86	274.77	5.26	43.96	56.0-57.0	0.20	621.10	0.03	99.36
10.0-11.0	29.74	304.51	4.76	48.71	57.0-58.0	0.17	621.27	0.03	99.39
11.0-12.0	26.42	330.94	4.23	52.94	58.0-59.0	0.14	621.41	0.02	99.41
12.0-13.0	23.30	354.23	3.73	56.67	59.0-60.0	0.12	621.53	0.02	99.43
13.0-14.0	20.65	374.88	3.30	59.97	60.0-61.0	0.09	621.62	0.02	99.45
14.0-15.0	18.63	393.51	2.98	62.95	61.0-62.0	0.08	621.70	0.01	99.46
15.0-16.0	17.18	410.69	2.75	65.70	62.0-63.0	0.06	621.75	0.01	99.47
16.0-17.0	16.16	426.85	2.59	68.29	63.0-64.0	0.04	621.80	0.01	99.47
17.0-18.0	15.40	442.25	2.46	70.75	64.0-65.0	0.03	621.83	0.00	99.48
18.0-19.0	14.77	457.03	2.36	73.11	65.0-66.0	0.02	621.84	0.00	99.48
19.0-20.0	14.20	471.23	2.27	75.39	66.0-67.0	0.01	621.85	0.00	99.48
20.0-21.0	13.64	484.87	2.18	77.57	67.0-68.0	0.00	621.86	0.00	99.48
21.0-22.0	13.05	497.92	2.09	79.66	68.0-69.0	0.00	621.86	0.00	99.48
22.0-23.0	12.38	510.30	1.98	81.64	69.0-70.0	0.00	621.86	0.00	99.48
23.0-24.0	11.62	521.92	1.86	83.50	70.0-71.0	0.00	621.86	0.00	99.48
24.0-25.0	10.81	532.74	1.73	85.23	71.0-72.0	0.00	621.86	0.00	99.48
25.0-26.0	10.00	542.73	1.60	86.82	72.0-73.0	0.00	621.86	0.00	99.48
26.0-27.0	9.18	551.91	1.47	88.29	73.0-74.0	0.00	621.86	0.00	99.48
27.0-28.0	8.37	560.28	1.34	89.63	74.0-75.0	0.00	621.86	0.00	99.48
28.0-29.0	7.58	567.86	1.21	90.85	75.0-76.0	0.00	621.86	0.00	99.48
29.0-30.0	6.73	574.60	1.08	91.92	76.0-77.0	0.00	621.86	0.00	99.48
30.0-31.0	5.76	580.35	0.92	92.84	77.0-78.0	0.00	621.86	0.00	99.48
31.0-32.0	4.84	585.19	0.77	93.62	78.0-79.0	0.00	621.86	0.00	99.48
32.0-33.0	4.14	589.33	0.66	94.28	79.0-80.0	0.00	621.86	0.00	99.48
33.0-34.0	3.63	592.96	0.58	94.86	80.0-81.0	0.00	621.86	0.00	99.48
34.0-35.0	3.22	596.18	0.52	95.38	81.0-82.0	0.00	621.86	0.00	99.48
35.0-36.0	2.88	599.06	0.46	95.84	82.0-83.0	0.00	621.86	0.00	99.48
36.0-37.0	2.59	601.66	0.41	96.25	83.0-84.0	0.00	621.86	0.00	99.48
37.0-38.0	2.34	604.00	0.37	96.63	84.0-85.0	0.00	621.86	0.00	99.48
38.0-39.0	2.12	606.12	0.34	96.97	85.0-86.0	0.00	621.86	0.00	99.48
39.0-40.0	1.91	608.03	0.31	97.27	86.0-87.0	0.00	621.86	0.00	99.48
40.0-41.0	1.71	609.75	0.27	97.55	87.0-88.0	0.00	621.86	0.00	99.48
41.0-42.0	1.53	611.27	0.24	97.79	88.0-89.0	0.00	621.86	0.00	99.48
42.0-43.0	1.36	612.63	0.22	98.01	89.0-90.0	0.00	621.86	0.00	99.48
43.0-44.0	1.21	613.84	0.19	98.20	90.0-91.0	0.00	621.86	0.00	99.48
44.0-45.0	1.08	614.93	0.17	98.37	91.0-92.0	0.00	621.86	0.00	99.48
45.0-46.0	0.97	615.90	0.16	98.53	92.0-93.0	0.00	621.86	0.00	99.48
46.0-47.0	0.87	616.76	0.14	98.67	93.0-94.0	0.00	621.86	0.00	99.48


Photometric Filename:UL-9W-COB-0900-BH-23度.IES

Zonal Flux Tabulation - (Cont.)

Zone(γ)	Zone Flux (1m)	Sums Flux (1m)	Zone%Lamp	Sums%Lamp	Zone(γ)	Zone Flux (1m)	Sums Flux (1m)	Zone%Lamp	Sums%Lamp
94.0-95.0	0.00	621.86	0.00	99.48	141.0-142.0	0.00	621.86	0.00	99.48
95.0-96.0	0.00	621.86	0.00	99.48	142.0-143.0	0.00	621.86	0.00	99.48
96.0-97.0	0.00	621.86	0.00	99.48	143.0-144.0	0.01	621.86	0.00	99.48
97.0-98.0	0.00	621.86	0.00	99.48	144.0-145.0	0.01	621.88	0.00	99.49
98.0-99.0	0.00	621.86	0.00	99.48	145.0-146.0	0.02	621.90	0.00	99.49
99.0-100.0	0.00	621.86	0.00	99.48	146.0-147.0	0.04	621.94	0.01	99.50
100.0-101.0	0.00	621.86	0.00	99.48	147.0-148.0	0.05	621.99	0.01	99.50
101.0-102.0	0.00	621.86	0.00	99.48	148.0-149.0	0.06	622.05	0.01	99.51
102.0-103.0	0.00	621.86	0.00	99.48	149.0-150.0	0.08	622.13	0.01	99.53
103.0-104.0	0.00	621.86	0.00	99.48	150.0-151.0	0.09	622.21	0.01	99.54
104.0-105.0	0.00	621.86	0.00	99.48	151.0-152.0	0.10	622.32	0.02	99.56
105.0-106.0	0.00	621.86	0.00	99.48	152.0-153.0	0.11	622.43	0.02	99.57
106.0-107.0	0.00	621.86	0.00	99.48	153.0-154.0	0.12	622.55	0.02	99.59
107.0-108.0	0.00	621.86	0.00	99.48	154.0-155.0	0.13	622.68	0.02	99.61
108.0-109.0	0.00	621.86	0.00	99.48	155.0-156.0	0.14	622.82	0.02	99.64
109.0-110.0	0.00	621.86	0.00	99.48	156.0-157.0	0.14	622.96	0.02	99.66
110.0-111.0	0.00	621.86	0.00	99.48	157.0-158.0	0.15	623.11	0.02	99.68
111.0-112.0	0.00	621.86	0.00	99.48	158.0-159.0	0.15	623.26	0.02	99.71
112.0-113.0	0.00	621.86	0.00	99.48	159.0-160.0	0.15	623.41	0.02	99.73
113.0-114.0	0.00	621.86	0.00	99.48	160.0-161.0	0.15	623.55	0.02	99.75
114.0-115.0	0.00	621.86	0.00	99.48	161.0-162.0	0.15	623.70	0.02	99.78
115.0-116.0	0.00	621.86	0.00	99.48	162.0-163.0	0.14	623.84	0.02	99.80
116.0-117.0	0.00	621.86	0.00	99.48	163.0-164.0	0.14	623.98	0.02	99.82
117.0-118.0	0.00	621.86	0.00	99.48	164.0-165.0	0.13	624.11	0.02	99.84
118.0-119.0	0.00	621.86	0.00	99.48	165.0-166.0	0.12	624.23	0.02	99.86
119.0-120.0	0.00	621.86	0.00	99.48	166.0-167.0	0.12	624.35	0.02	99.88
120.0-121.0	0.00	621.86	0.00	99.48	167.0-168.0	0.11	624.46	0.02	99.90
121.0-122.0	0.00	621.86	0.00	99.48	168.0-169.0	0.10	624.56	0.02	99.92
122.0-123.0	0.00	621.86	0.00	99.48	169.0-170.0	0.09	624.65	0.01	99.93
123.0-124.0	0.00	621.86	0.00	99.48	170.0-171.0	0.08	624.74	0.01	99.94
124.0-125.0	0.00	621.86	0.00	99.48	171.0-172.0	0.08	624.81	0.01	99.96
125.0-126.0	0.00	621.86	0.00	99.48	172.0-173.0	0.07	624.88	0.01	99.97
126.0-127.0	0.00	621.86	0.00	99.48	173.0-174.0	0.06	624.94	0.01	99.98
127.0-128.0	0.00	621.86	0.00	99.48	174.0-175.0	0.05	624.98	0.01	99.98
128.0-129.0	0.00	621.86	0.00	99.48	175.0-176.0	0.04	625.02	0.01	99.99
129.0-130.0	0.00	621.86	0.00	99.48	176.0-177.0	0.03	625.05	0.00	99.99
130.0-131.0	0.00	621.86	0.00	99.48	177.0-178.0	0.02	625.07	0.00	100.00
131.0-132.0	0.00	621.86	0.00	99.48	178.0-179.0	0.01	625.09	0.00	100.00
132.0-133.0	0.00	621.86	0.00	99.48	179.0-180.0	0.00	625.09	0.00	100.00
133.0-134.0	0.00	621.86	0.00	99.48					
134.0-135.0	0.00	621.86	0.00	99.48					
135.0-136.0	0.00	621.86	0.00	99.48					
136.0-137.0	0.00	621.86	0.00	99.48					
137.0-138.0	0.00	621.86	0.00	99.48					
138.0-139.0	0.00	621.86	0.00	99.48					
139.0-140.0	0.00	621.86	0.00	99.48					
140.0-141.0	0.00	621.86	0.00	99.48					

Rectangle ISO Lighting Intensity Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14




Maximum Light Intensity(cd): 4624.53
Maximum Cand.@Angle: H=0.0°,V=0.0°

Photometric Filename:UL-9W-COB-0900-BH-23度.IES

Plane ISO-Illuminance Diagram

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14

Plane ISO-Illuminance Curve



Working Plane Luminaire Mounting Height(m): 3.00


Working Plane Maximum Illuminance(lx): 513.84

Working Plane Maximum Illuminance Position(d/h):H0.0 V0.0

3D Plane ISO Illuminance Diagram

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14


3D Plane Illuminance Modal



Space ISO Illuminance Diagram

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14


Space ISO Illuminance Curve



Space Plane Maximum Illuminance and @Angle:4624.53lx,0.0deg
Plane Maximum Lighting Intensity and @Angle:4624.529cd,0eg

Illuminance-Distance Diagram

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14



Indoor Luminance Limiting Curves

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14


Glare Grade Table

GI	Quality	Using Illuminance							
1.15	A	2000	1000	500	<=300				
1.5	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.2	D				2000	1000	500	<=300	
2.55	E	a				2000	1000	500	<=300
			b	c	d	e	f	g	h

Luminance Table

Gama (deg)	45	50	55	60	65	70	75	80	85
C0	9443	4953	2608	1170	336	0	0	0	0
C90	10638	5835	3046	1406	443	0	0	0	0

Luminance Limiting Curve




Luminous Size:Length(m)=-0.050Width(m)=-0.050Height(m)=0.000Area(m^2)=0.001963

Luminous Type:Without Luminous Side

Luminous Curves:C0-C180 Color: C90-C270 Color:

Indoor Budgetary Estimate Table

Lum. Name: 55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14



Indoor Coefficient of Utilization Table

Lum. Name:55252	Lum. Catelog:	Test ID:
Lamp Name:	Lamp Catelog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14

Coefficients of Utilization – Zonal Cavity Method																		
Coef.	Effective Floor Cavity Reflectance RFC=0.20																	
RhoCC (%)	80				70				50			30			10			0
RhoW (%)	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR	Coefficient of Utilization(%)																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	99
1	115	113	111	109	113	111	109	108	107	105	104	103	102	101	99	99	98	96
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	97	96	95	93
3	108	103	100	97	106	102	99	96	99	97	94	97	95	93	95	93	91	90
4	104	99	95	92	103	98	94	92	96	93	91	94	92	90	92	90	89	87
5	101	96	92	89	100	95	91	88	93	90	87	92	89	87	90	88	86	85
6	99	92	88	85	97	92	88	85	90	87	85	89	86	84	88	85	83	82
7	96	90	86	83	95	89	85	82	88	84	82	87	84	82	86	83	81	80
8	93	87	83	80	92	87	83	80	86	82	80	85	82	79	84	81	79	78
9	91	85	81	78	90	84	80	78	83	80	78	83	80	77	82	79	77	76
10	89	82	79	76	88	82	78	76	81	78	76	81	78	76	80	77	75	74

Unified Glare Rating Table

Lum. Name:55252	Lum. Catalog:	Test ID:
Lamp Name:	Lamp Catalog:	Test Lab:
Manufacture:	Test Machine:GON-2000	Test Date: 2023/03/14

Unified Glare Rating Table

Ceiling RCC		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
Wall RW		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
Floor RFC		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room Size		Vewed crosswise					Vewed endwise				
X=2H	Y=2H	11.7	12.6	12.0	12.9	13.2	12.6	13.5	13.0	13.8	14.2
	Y=3H	11.5	12.2	11.8	12.6	13.0	12.4	13.2	12.8	13.5	13.9
	Y=4H	11.3	12.1	11.8	12.4	12.8	12.3	13.0	12.7	13.4	13.8
	Y=6H	11.2	11.9	11.7	12.3	12.7	12.2	12.8	12.6	13.2	13.6
	Y=8H	11.2	11.8	11.6	12.2	12.6	12.1	12.7	12.6	13.1	13.6
	Y=12H	11.1	11.7	11.5	12.1	12.5	12.0	12.6	12.5	13.0	13.5
X=4H	Y=2H	11.4	12.1	11.8	12.5	12.9	12.3	13.0	12.7	13.4	13.8
	Y=3H	11.1	11.7	11.6	12.1	12.6	12.1	12.7	12.5	13.1	13.5
	Y=4H	11.0	11.5	11.5	12.0	12.4	11.9	12.5	12.4	12.9	13.4
	Y=6H	10.9	11.3	11.4	11.8	12.3	11.8	12.3	12.3	12.7	13.2
	Y=8H	10.8	11.2	11.3	11.7	12.2	11.8	12.2	12.2	12.6	13.1
	Y=12H	10.7	11.1	11.2	11.6	12.1	11.7	12.0	12.2	12.5	13.0
X=8H	Y=4H	10.8	11.2	11.3	11.7	12.2	11.8	12.2	12.2	12.6	13.1
	Y=6H	10.7	11.0	11.2	11.5	12.0	11.6	11.9	12.1	12.5	13.0
	Y=8H	10.6	10.9	11.1	11.4	11.9	11.5	11.8	12.1	12.4	12.9
	Y=12H	10.5	10.8	11.1	11.3	11.9	11.5	11.7	12.0	12.2	12.8
X=12H	Y=4H	10.7	11.1	11.2	11.6	12.1	11.7	12.0	12.2	12.5	13.0
	Y=6H	10.6	10.9	11.2	11.4	11.9	11.5	11.8	12.1	12.3	12.9
	Y=8H	10.5	10.8	11.1	11.3	11.9	11.5	11.7	12.0	12.2	12.8
Variations with the objverver position at spacings											
S=1.0H		0.0/0.0					0.0/0.0				
S=1.5H		0.0/0.0					0.0/0.0				
S=2.0H		9.1/0.0					8.6/0.0				
Reduced UGR Table:											
Nordic Standard Table:		BK0					BK0				
Correction Value		0.0					0.0				

o the CIE Pub.117, data has been corrected, refers to the lamp's lumens 8.2flm.

IES Indoor Report

Photometric Filename:UL-9W-COB-0900-BH-23度.IES

Candela Tabulation

V/H	C0. 0	C30. 0	C60. 0	C90. 0	C120. 0	C150. 0	C180. 0	C210. 0	C240. 0	C270. 0	C300. 0	C330. 0
γ 0. 0	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53	4624. 53
γ 1. 0	4562. 41	4543. 70	4573. 23	4542. 49	4566. 90	4524. 02	4604. 37	4601. 49	4587. 17	4597. 37	4582. 38	4595. 67
γ 2. 0	4390. 79	4362. 65	4411. 22	4370. 98	4414. 54	4354. 12	4484. 72	4482. 13	4446. 47	4465. 53	4437. 54	4479. 95
γ 3. 0	4138. 69	4104. 96	4177. 93	4138. 79	4185. 78	4116. 52	4277. 43	4280. 40	4228. 16	4255. 85	4210. 22	4281. 58
γ 4. 0	3834. 41	3788. 03	3879. 15	3838. 94	3893. 22	3811. 48	4007. 90	4014. 98	3931. 41	3969. 85	3916. 84	4010. 65
γ 5. 0	3484. 20	3439. 20	3539. 89	3500. 82	3555. 37	3461. 50	3680. 15	3680. 18	3576. 83	3632. 51	3564. 06	3672. 61
γ 6. 0	3091. 00	3062. 11	3164. 03	3124. 45	3185. 41	3082. 86	3304. 27	3298. 02	3179. 22	3253. 36	3166. 84	3279. 02
γ 7. 0	2684. 41	2668. 55	2774. 23	2737. 93	2788. 28	2682. 15	2899. 65	2886. 58	2762. 04	2831. 94	2752. 96	2860. 13
γ 8. 0	2281. 99	2274. 58	2387. 83	2352. 65	2399. 32	2297. 39	2493. 54	2473. 66	2343. 99	2402. 91	2332. 16	2440. 91
γ 9. 0	1904. 86	1901. 03	2009. 61	1983. 38	2025. 16	1936. 00	2107. 32	2078. 59	1952. 22	2004. 41	1939. 16	2038. 61
γ 10. 0	1566. 16	1567. 94	1661. 62	1648. 02	1681. 47	1606. 75	1747. 41	1718. 91	1596. 00	1640. 21	1583. 59	1668. 45
γ 11. 0	1272. 71	1285. 80	1362. 63	1351. 77	1382. 21	1315. 38	1426. 52	1399. 30	1287. 91	1323. 25	1269. 75	1349. 47
γ 12. 0	1031. 58	1051. 66	1117. 66	1111. 63	1129. 08	1066. 66	1152. 78	1127. 91	1033. 60	1060. 24	1018. 20	1079. 90
γ 13. 0	838. 43	868. 64	923. 11	925. 41	924. 89	872. 36	932. 30	909. 33	834. 07	853. 32	824. 61	869. 01
γ 14. 0	697. 22	731. 03	779. 48	784. 05	770. 42	725. 25	765. 92	745. 18	685. 27	700. 03	684. 02	714. 47
γ 15. 0	601. 58	633. 72	677. 98	677. 10	660. 77	620. 55	647. 11	629. 01	575. 48	587. 64	582. 35	605. 50
γ 16. 0	533. 93	566. 69	604. 67	601. 00	578. 89	545. 32	559. 59	544. 57	495. 12	506. 13	508. 01	528. 54
γ 17. 0	481. 33	515. 44	551. 05	542. 86	518. 51	489. 24	496. 83	482. 02	434. 31	445. 95	451. 79	472. 09
γ 18. 0	437. 89	475. 27	507. 35	497. 71	470. 29	443. 93	448. 99	432. 14	386. 61	396. 69	405. 31	427. 49
γ 19. 0	400. 58	439. 33	467. 83	457. 68	431. 23	406. 11	408. 49	390. 20	347. 98	356. 43	365. 88	389. 27
γ 20. 0	366. 72	404. 11	433. 88	424. 14	396. 49	373. 17	369. 98	354. 73	316. 63	322. 29	333. 24	353. 44
γ 21. 0	335. 16	372. 13	400. 68	391. 45	365. 29	341. 28	337. 10	324. 31	289. 99	292. 21	305. 01	322. 10
γ 22. 0	305. 07	339. 74	368. 42	356. 77	333. 33	310. 66	308. 46	295. 40	263. 10	264. 31	279. 26	292. 61
γ 23. 0	276. 31	310. 26	336. 16	320. 26	302. 01	281. 57	280. 31	266. 55	238. 16	236. 07	250. 37	264. 99
γ 24. 0	247. 85	281. 39	305. 25	287. 97	271. 53	251. 90	252. 95	237. 48	213. 71	207. 98	220. 40	236. 88
γ 25. 0	220. 26	253. 65	276. 21	260. 39	245. 10	223. 88	225. 63	210. 03	191. 21	183. 54	192. 68	209. 19
γ 26. 0	195. 34	226. 78	247. 72	233. 64	219. 90	197. 60	200. 00	183. 87	169. 81	162. 04	168. 42	184. 21
γ 27. 0	171. 76	202. 59	221. 56	207. 16	195. 23	173. 02	175. 38	162. 95	150. 03	143. 10	147. 60	162. 00
γ 28. 0	150. 89	177. 73	195. 69	181. 37	170. 63	149. 77	152. 62	144. 38	133. 18	126. 77	129. 75	142. 47
γ 29. 0	131. 91	153. 36	170. 68	156. 98	148. 04	129. 33	133. 01	127. 71	118. 78	113. 36	114. 69	124. 73
γ 30. 0	107. 26	123. 88	139. 67	128. 30	124. 04	108. 64	114. 97	111. 78	105. 83	101. 02	100. 04	104. 59
γ 31. 0	89. 01	103. 49	116. 34	106. 89	103. 49	87. 58	92. 91	89. 79	85. 81	80. 82	76. 17	80. 55
γ 32. 0	74. 98	86. 39	96. 67	89. 85	86. 85	72. 37	74. 22	70. 73	67. 35	63. 28	62. 60	67. 42
γ 33. 0	63. 40	71. 79	80. 56	75. 55	73. 49	61. 21	62. 51	59. 93	57. 62	54. 86	54. 95	58. 24
γ 34. 0	54. 69	60. 14	67. 22	63. 23	62. 31	53. 24	53. 90	52. 15	50. 05	48. 36	48. 62	51. 56
γ 35. 0	47. 79	51. 06	56. 58	53. 91	53. 44	46. 81	47. 22	46. 05	44. 11	43. 07	43. 11	45. 71
γ 36. 0	41. 82	44. 21	48. 32	46. 67	45. 93	41. 32	41. 70	40. 96	39. 15	38. 46	38. 16	40. 33
γ 37. 0	36. 69	38. 74	41. 85	40. 77	40. 09	36. 51	36. 89	36. 58	34. 90	34. 49	34. 01	35. 48
γ 38. 0	32. 35	34. 11	36. 65	35. 86	35. 12	32. 25	32. 72	32. 59	31. 17	30. 95	30. 45	31. 47
γ 39. 0	28. 62	30. 10	32. 01	31. 45	30. 84	28. 57	29. 15	29. 05	27. 67	27. 44	27. 14	28. 02
γ 40. 0	25. 15	26. 55	28. 07	27. 54	27. 01	25. 19	25. 89	25. 65	24. 30	24. 07	23. 81	24. 74
γ 41. 0	22. 02	23. 06	24. 62	24. 17	23. 66	22. 09	22. 80	22. 42	21. 13	20. 96	20. 68	21. 59
γ 42. 0	19. 29	20. 19	21. 64	21. 26	20. 79	19. 44	19. 92	19. 56	18. 38	18. 22	17. 89	18. 72
γ 43. 0	16. 83	17. 61	18. 82	18. 60	18. 15	16. 95	17. 42	17. 00	16. 02	15. 94	15. 48	16. 24
γ 44. 0	14. 83	15. 64	16. 62	16. 55	16. 03	14. 79	15. 10	14. 72	13. 87	13. 85	13. 44	14. 11
γ 45. 0	13. 11	13. 89	14. 76	14. 77	14. 20	13. 07	13. 15	12. 82	12. 07	12. 08	11. 78	12. 48
γ 46. 0	11. 60	12. 28	13. 06	13. 05	12. 56	11. 53	11. 55	11. 19	10. 57	10. 62	10. 37	11. 05

Photometric Filename:UL-9W-COB-0900-BH-23度.IES

Candela Tabulation - (Cont.)

[illegible]

Photometric Filename:UL-9W-COB-0900-BH-23度.IES

[illegible]

Candela Tabulation - (Cont.)

V/H	C0.0	C30.0	C60.0	C90.0	C120.0	C150.0	C180.0	C210.0	C240.0	C270.0	C300.0	C330.0
γ 141.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
γ 142.0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.00	0.00
γ 143.0	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.10	0.16	0.15	0.13	0.06
γ 144.0	0.05	0.00	0.00	0.00	0.00	0.00	0.20	0.27	0.32	0.32	0.30	0.23
γ 145.0	0.23	0.17	0.10	0.09	0.09	0.16	0.38	0.45	0.51	0.51	0.48	0.41
γ 146.0	0.43	0.35	0.29	0.26	0.28	0.35	0.59	0.65	0.71	0.71	0.69	0.62
γ 147.0	0.64	0.58	0.50	0.48	0.49	0.56	0.82	0.87	0.94	0.95	0.93	0.85
γ 148.0	0.87	0.80	0.72	0.69	0.71	0.78	1.07	1.13	1.20	1.19	1.19	1.10
γ 149.0	1.12	1.05	0.97	0.96	0.95	1.04	1.33	1.38	1.46	1.46	1.46	1.37
γ 150.0	1.40	1.32	1.24	1.23	1.22	1.32	1.61	1.67	1.74	1.73	1.74	1.64
γ 151.0	1.69	1.63	1.52	1.52	1.51	1.60	1.90	1.95	2.03	2.02	2.03	1.93
γ 152.0	1.98	1.90	1.81	1.80	1.79	1.89	2.20	2.25	2.32	2.32	2.33	2.22
γ 153.0	2.26	2.18	2.10	2.08	2.08	2.18	2.49	2.54	2.60	2.60	2.60	2.52
γ 154.0	2.55	2.46	2.39	2.37	2.37	2.47	2.77	2.82	2.88	2.89	2.88	2.80
γ 155.0	2.82	2.75	2.67	2.65	2.65	2.74	3.04	3.09	3.13	3.14	3.15	3.06
γ 156.0	3.10	3.03	2.93	2.92	2.92	3.01	3.30	3.33	3.37	3.38	3.40	3.32
γ 157.0	3.34	3.27	3.16	3.16	3.16	3.25	3.53	3.55	3.58	3.61	3.62	3.54
γ 158.0	3.56	3.47	3.38	3.39	3.40	3.48	3.74	3.74	3.77	3.80	3.82	3.74
γ 159.0	3.77	3.68	3.57	3.60	3.60	3.67	3.94	3.94	3.92	3.96	4.00	3.92
γ 160.0	3.95	3.86	3.74	3.79	3.80	3.88	4.10	4.09	4.06	4.11	4.16	4.09
γ 161.0	4.11	4.01	3.91	3.94	3.97	4.03	4.24	4.22	4.16	4.23	4.28	4.23
γ 162.0	4.26	4.14	4.04	4.09	4.12	4.18	4.37	4.32	4.24	4.32	4.39	4.34
γ 163.0	4.38	4.26	4.16	4.21	4.25	4.30	4.48	4.41	4.30	4.39	4.47	4.44
γ 164.0	4.48	4.36	4.26	4.33	4.35	4.41	4.56	4.46	4.35	4.45	4.57	4.51
γ 165.0	4.55	4.45	4.34	4.41	4.46	4.49	4.64	4.52	4.39	4.48	4.61	4.60
γ 166.0	4.63	4.51	4.42	4.49	4.54	4.57	4.70	4.57	4.42	4.51	4.66	4.66
γ 167.0	4.69	4.56	4.49	4.55	4.60	4.65	4.74	4.59	4.45	4.54	4.67	4.69
γ 168.0	4.73	4.60	4.53	4.59	4.67	4.71	4.77	4.62	4.46	4.55	4.70	4.73
γ 169.0	4.76	4.64	4.58	4.61	4.69	4.74	4.79	4.61	4.48	4.54	4.69	4.74
γ 170.0	4.77	4.65	4.59	4.63	4.71	4.75	4.79	4.63	4.48	4.53	4.68	4.74
γ 171.0	4.75	4.65	4.60	4.63	4.71	4.74	4.77	4.61	4.48	4.50	4.64	4.71
γ 172.0	4.72	4.63	4.60	4.61	4.68	4.71	4.75	4.59	4.46	4.49	4.59	4.67
γ 173.0	4.68	4.61	4.57	4.57	4.63	4.67	4.68	4.55	4.45	4.45	4.54	4.61
γ 174.0	4.63	4.57	4.54	4.54	4.58	4.61	4.63	4.52	4.42	4.43	4.49	4.55
γ 175.0	4.59	4.53	4.50	4.49	4.52	4.55	4.58	4.48	4.41	4.38	4.43	4.48
γ 176.0	4.54	4.49	4.46	4.44	4.46	4.49	4.52	4.45	4.38	4.36	4.39	4.45
γ 177.0	4.50	4.46	4.43	4.40	4.42	4.46	4.49	4.42	4.38	4.35	4.37	4.41
γ 178.0	4.49	4.45	4.40	4.38	4.39	4.43	4.47	4.43	4.39	4.36	4.36	4.41
γ 179.0	4.47	4.44	4.39	4.37	4.39	4.43	4.47	4.43	4.40	4.36	4.38	4.42
γ 180.0	4.43	4.43	4.43	4.43	4.43	4.43	4.43	4.43	4.43	4.43	4.43	4.43