Ventilated | Low speed | Benchtop

TD-420



The TD-420 offers exceptional user comfort and a choice of 4 rotors, including the most popular swing out rotors for 15ml and 50ml tube. It adopts intelligent LCD touch screen, easily operate with gloves. Thanks to the strong operation system, it supports the multi-stage centrifugation and can store up to 1000 programs.

FEATURES

User-friendly functions

- >up to 1000 user-defined programs
- >up to 1000 run histories, can be exported via USB
- >up to 40 rates acceleration and deceleration
- >up to 5 stages multi-stage centrifugation mode available
- >up to 99h59m59s timer range, 1s increment

Ensure safety

- >Microprocessor control
- >Motorized electronic door lock
- >Door cannot be opened when rotor is spinning
- >Gas hinge to prevent door falling
- >Port in the door for calibration and operation checking
- >Emergency door lock release
- >Password to lock the device

LCD touch screen

- >Simple and clear to show all parameters
- >Touch screen, easy to set parameters
- >RCF can be set directly
- >RPM and RCF covert automatically
- >User can set parameters even with gloves
- >User can reset parameters when rotor is spinning

Good components

>Motor: Variable frequency motor.

stable running, maintenance free, long life

- >Housing: Thick and strong steel
- >Chamber: Food grade 304 stainless steel.
 - anticorrosion and easy to clean
- >Rotor: Stainless steel swing out rotor.
- >Rotors are autoclavable

TECHNICAL DATA

Max Speed	4200rpm
Max RCF	3285xg
Max Capacity	4x100ml
Speed Accuracy	±10rpm
Time Setting	1s ~ 99h59m59s

Acc/Dec Rate	40 rates
Noise	≤60dB(A)
Power Consumption	500w
Dimension	495x400x420mm
Weight	27kg

AVAILABLE ROTORS







