

Ventilated | High speed | Benchtop



# TG-15

- ## Features
- >12 user-defined programs
  - >10 rates acceleration and deceleration
  - >LED screen shows RPM/RCF and Time
  - >RCF can be set directly
  - >1min to 99min59s timer range
  - >User can reset parameters when rotor is spinning
  - >Variable frequency motor drive
  - >Microprocessor control
  - >Electronic lid lock, controlled by independent motor
  - >Steel housing;304 stainless steel chamber



## TECHNICAL DATA

Max Speed	15000rpm	Noise	≤58dB(A)
Max RCF	21630xg	Voltage	220v/110v
Max Capacity	12x5ml	Power Consumption	500w
Speed Accuracy	±20rpm	Dimension	410x300x260mm
Time Setting	1m ~ 99m59s/pulse	Weight	18kg

## AVAILABLE ROTORS

Fixed angle rotor					
Rotor	Capacity	Order No.	Max speed/RCF	Adaptor	
				Capacity	Order No.
	24×1.5/2ml (aerosol tight)	0494021100	15000rpm/21630×g	24×1×0.2ml	1101010001
				24×1×0.5ml	1101010002
	12×5ml (aerosol tight)	0494030400	15000rpm/18240×g	12×1×1.8ml frozen storage tube	1101020002
				12×1×2ml frozen storage tube	1101020004
				12×1×2ml	1101020001
	4×8×0.2ml PCR strip (aerosol tight)	0494010300	15000rpm/19600×g	/	/