



BSL Series

B-LFP36-100

to replace lead acid GEL Or AGM



PRODUCT FEATURES



Designed for Power Energy Storage, Marine, RV, UPS, Lawn Mowers, Fish Finders, Access Control Systems, and House Alarm Security applications, BSLBATT's 36V 3840Wh lithium batteries last up to four times longer than lead-acid batteries. They are maintenance-free, lightweight, and easy to operate.

Our B-LFP36-100 model is equipped with the industry's leading LFP battery technology, featuring the safest lithium battery chemistry available today. This makes it an ideal choice for deep-cycle applications.

CHARGE AND DISCHARGE CURVE

DIMENSION

38.4V 100Ah Charge-Discharge Curve 0.5C, 25°C



Certification: UL, FCC, CE, ROHS, UN38.3, IEC

Battery Model

B-LFP36-100

Nominal Voltage	38.4 V
Typical Capacity	100 Ah
Energy	3840 Wh

Discharge

Working Current	0.5 C
Maximum Current	1 C
Cut-off Voltage	About 30 V

Charge

Voltage	43.2 ± 0.1 V
Working Current	0.5 C
Max Charging Current	≤ 1 C
Charge Mode	CC/CV, please use special lithium charger
Charging Cut-off Current	About 5 A

Operation Temperature

Charge	0°C ~ +55°C
Discharge	-20°C ~ +60°C

Additional Data

Storage Temperature	-20°C ~ +45°C
Discharging Inner Resistance	≤ 60 mΩ
Protection Function	Overcharge, over-discharge, over-current, short circuit and other protection functions
Output Mode	M8 Terminal
Shell Material	ABS
Weight	30.47 Kg
Dimension (L*W*H)	520*268*219 (±2) mm
Serial-parallel module	1P12S
Cycle	≥3500@ 80%DOD (0.5C, 25°C)

Note: Parameters can be adjusted according to customer requirements



Facebook



Linkedin



Tiktok



Instagram



Youtube



Drop-in Replacement



Tier One, A+ LiFePO4 Cell Composition



5 Years Warranty Guarantee



Smart Hardware & Software Design



Long Service Life



Eco-Friendly