

# Titan Series-3060

Mitsubishi car engine

High pressure pump

Multifunctional control remote control

## Titan Series

### TS3060

Pressure: 4350 psi | 60 L/min  
 High-pressure Pump:  
 German PERFECT POWER stainless steel  
 Gear Box: German PERFECT POWER  
 Engine:  
 Mitsubishi 2.0T 100 HP gasoline engine (automobile engine)  
 Remote Control Functions: YES  
 Left Hose Length:  
**75M** FlexPro™ Hose (Bulletproof Material) | Inner Diameter: 13mm  
 Right Hose Length:  
**75M** FlexPro™ Hose (Bulletproof Material) | Inner Diameter: 10mm  
 Bottom Reel: Garden hose for water tank filling  
 System: RS4 Remote Control system  
 Remote Controller:  
 OLED screen remote controller

Hose Thread:  
**Left side 1/2, Right side 1/4**

### Applicable pipes

**2-34 inch**

made in China

**1**  
1 year warranty

Single person operation

Rs4 system

### TS3060

Bulletproof vest material hose

200-meter remote control range in open areas.

## Nozzle Selection Guide

### Commercial Model

Inner Diameter: 13mm | 1/2" NPT Thread  
 Suitable for Pipe Diameters:  
 DN110 / DN150 / DN160 / DN200 / DN300  
 Operating Pressure: 300 bar  
 Flow Rate: 60 L/min

**Diamond Drill Nozzle**  
 The front three holes spray water to treat municipal sludge clogging the pipes. The rear six holes discharge water to provide hose propulsion.

**Rocket Nozzle**  
 One in front and six in back. The water spray angle at the rear is particularly small, with the water spray concentrated toward the rear to generate maximum thrust. Suitable for long-distance pipeline propulsion.

**Pro Low-Angle Jet Nozzle**  
 The rear spray angle is small, and there are more water outlets. Suitable for large-area flushing pipes. Suitable for long-distance hose advancement.

**Root Cutting Nozzle**  
 The front turbine rotates, causing the water to swirl and break up heavy blockages of grease and tree roots ahead.

**Penetrator Pro**  
 Rotating nozzle, special alloy material, for handling minor concrete or cement clumps or heavy grease blockages

### Residential Model

Inner Diameter: 8mm | 1/4" NPT Thread  
 Compatible Pipe Sizes:  
 DN50 / DN60 / DN75 / DN110  
 Operating Pressure: 300 bar  
 Flow Rate: 30 L/min

**Root Cutting Nozzle**  
 Treating tree roots and stubborn grease in residential building main pipes

**Mushroom Nozzle**  
 Standard nozzle, suitable for cleaning residential sewer blockages

**Mini Low-Angle Jet Nozzle**  
 The rear spray angle is small, and there are more water outlets. Suitable for large-area flushing pipes. Suitable for long-distance hose advancement.

**Thumb Nozzle**  
 The exterior design is relatively rounded, allowing it to turn in smaller pipes. When turning, its rounded design prevents it from getting stuck in the pipe

AMJET provides radio-controlled sewer jetting systems and pipe cleaning tools, built to European standards for professionals.