


**MODEL: HC-1200GF**

**400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>1650 kVA</b>	<b>PRP</b> Prime Power	<b>1500 kVA</b>
<b>ENGINE</b>	<b>CCEC Cummins</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>KTA50-GS8</b>		<b>S7L1D-C4</b>

## GENERAL FEATURES

Engine: CCEC Cummins KTA50-GS8

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: HC-1200GF**

**400V | 1500rpm | 50Hz**

### GENERATOR RATINGS

Voltage	Hz	Phase	PF ( COSΦ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	2165	1320/1650	1200/1500
415/240	50	3	0.8	2295	1320/1650	1200/1500
400/230	50	3	0.8	2381	1320/1650	1200/1500
380/220	50	3	0.8	2506	1320/1650	1200/1500

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 ( eqv ISO 8528 ) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

### SALES PROMISES

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

**MODEL: HC-1200GF****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	CCEC Cummins KTA50-GS8
Air intake system	Turbo, Air/Water cooling
Fuel system	PT type fuel pump, EFC
Cylinder arrangement	16 in "V"
Displacement	50.3L
Bore and stroke	159*159 (mm)
Compression ratio	14.9:1
Rated speed	1500rpm
Max. Standby power at rated speed	1429KW/1944HP
Governor type	Electronic

**Exhaust System**

Exhaust gas flow	261 m <sup>3</sup> /min
Exhaust temperature	510 °C
Max back pressure	7kPa

**Air Intake System**

Max intake restriction	6.23kPa
Combustion air flow	99.3 m <sup>3</sup> /min
Air flow required for radiator	1680 m <sup>3</sup> /min

**MODEL: HC-1200GF****400V | 1500rpm | 50Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	204 g/kWh	313 L/h
Fuel consumption @ 75% (Prime Power) Load	210 g/kWh	243 L/h
Fuel consumption @ 50% (Prime Power) Load	221 g/kWh	175 L/h

**Oil System**

Total oil capacity	204L
Oil consumption	≤4g/kwh
Oil sump capacity	148~178L

**Cooling System**

Coolant capacity	380L
Max water temperature	104°C

**MODEL: HC-1200GF****400V | 1500rpm | 50Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	1550kVA
Alternator Efficiency	95.4%

**MODEL: HC-1200GF** **400V | 1500rpm | 50Hz**

**GENERATING SET DATA**

Related range of voltage setting	≥±5%
Steady-state voltage deviation	≤±1%
Transient voltage deviation (100 % sudden power decrease)	≤+25%
Transient voltage deviation (sudden power increase)	≤-20%
Voltage recovery time (100 % sudden power decrease)	≤6S
Voltage recovery time (sudden power increase)	≤6S
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	≤1.5%
Transient frequency deviation (100 % sudden power decrease)	≤+12%
Transient frequency deviation (sudden power increase)	≤-10%
Frequency recovery time (100 % sudden power decrease)	≤5S
Frequency recovery time (sudden power increase)	≤5S

**STANDARD FEATURES**

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	Special tools



**MODEL: HC-1200GF**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 5550×2150×2550 mm

Weight: 11000 kg

**Soundproof Type (standard 20'ft HQ container)**

Overall Dimensions: 6058×2438×2896 mm

Weight: 16000 kg

*Specifications are subject to change without notice.*