

MODEL: HC-110GF-60

440V | 1800rpm | 60Hz



ESP Standby Power	125kVA	PRP Prime Power	114kVA
ENGINE	Perkins	ALTERNATOR	STAMFORD
	1104C-44TAG2		UCI274C1

GENERAL FEATURES

Engine: Perkins 1104C-44TAG2	Alternator: single bearing, IP23, insulation class H
50°C radiator, fans are driven by belt, with safety guard	Dry type air filter, fuel filter & oil filter
Vibration damper	Standard control panel
24V charging alternator	Exhaust bellows, elbows, flange & muffler
Lead-acid batteries, rack and cables	User manual

MODEL: HC-110GF-60**440V | 1800rpm | 60Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF (COS Φ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
480/277	60	3	0.8	150	100kW/125kVA	91kW/114kVA
460/266	60	3	0.8	157	100kW/125kVA	91kW/114kVA
440/254	60	3	0.8	164	100kW/125kVA	91kW/114kVA
416/240	60	3	0.8	173	100kW/125kVA	91kW/114kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

MODEL: HC-110GF-60**440V | 1800rpm | 60Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Perkins 1104C-44TAG2
Air intake system	Turbocharged, air-to-air charge cooled
Fuel system	Direct injection
Cylinder arrangement	4 in line
Displacement	4.4L
Bore and stroke	105×127 mm
Compression ratio	18.23
Rated speed	1800rpm
Max. Standby power at rated speed	117.5kW
Governor type	Electronic

Exhaust System

Exhaust gas flow	20.4 m ³ /min
Exhaust temperature	574°C
Max back pressure	15kPa

Air Intake System

Max intake restriction	8kPa
Combustion air flow	7.8 m ³ /min
Air flow required for radiator	225.6 m ³ /min

MODEL: HC-110GF-60**440V | 1800rpm | 60Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load 26.9 L/h

Fuel consumption @ 75% (Prime Power) Load 20.2 L/h

Fuel consumption @ 50% (Prime Power) Load 14.1 L/h

Oil System

Total oil capacity 8L

Oil sump capacity 5.5-7L

Oil consumption at full load as a % of fuel consumption 0.15%

Cooling System

Coolant capacity 13L

Max water temperature 110°C

MODEL: HC-110GF-60 **440V | 1800rpm | 60Hz**

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	117.5kVA
Alternator Efficiency	90.6%

MODEL: HC-110GF-60

440V | 1800rpm | 60Hz

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB

Base fuel tank



MODEL: HC-110GF-60

440V | 1800rpm | 60Hz

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

DIMENSIONS & WEIGHT



Standard Configuration (open type)
Overall Dimensions: 2150×900×1550 mm
Weight: 1250kg
Soundproof Type
Overall Dimensions: 2810×1140×1830 mm
Weight: 1700kg

Specifications are subject to change without notice.