


**MODEL: HC-1250GF**

**400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>1250 kVA</b>	<b>PRP</b> Prime Power	<b>1125 kVA</b>
<b>ENGINE</b>	<b>Perkins</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>4008-30TAG3</b>		<b>S6L1D-F4</b>

**GENERAL FEATURES**

Engine: Perkins 4008-30TAG3	Alternator: single bearing, IP23, insulation class H
50°C radiator, fans are driven by belt, with safety guard	Dry type air filter, fuel filter & oil filter
Vibration damper	Standard control panel
24V charging alternator	Exhaust bellows, elbows, flange & muffler
Lead-acid batteries, rack and cables	User manual

**MODEL: HC-1250GF****400V | 1500rpm | 50Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF ( COS $\Phi$ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	1640	1000kW/1250kVA	900kW/1125kVA
415/240	50	3	0.8	1739	1000kW/1250kVA	900kW/1125kVA
400/230	50	3	0.8	1804	1000kW/1250kVA	900kW/1125kVA
380/220	50	3	0.8	1899	1000kW/1250kVA	900kW/1125kVA

**Prime Power (PRP):** Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 ( eqv ISO 8528 ) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

**Standby Power Rating (ESP):** The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

**MODEL: HC-1250GF****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Perkins 4008-30TAG3
----------------------	---------------------

Air intake system	Turbocharged
-------------------	--------------

Fuel system	Direct Injection
-------------	------------------

Cylinder arrangement	8 in line
----------------------	-----------

Displacement	30.56L
--------------	--------

Bore and stroke	160×190 mm
-----------------	------------

Compression ratio	13:1
-------------------	------

Rated speed	1500rpm
-------------	---------

Max. Standby power at rated speed	1105kW
-----------------------------------	--------

Governor type	Electronic
---------------	------------

**Exhaust System**

Exhaust gas flow	240 m <sup>3</sup> /min
------------------	-------------------------

Exhaust temperature	482°C
---------------------	-------

Max back pressure	7.0kPa
-------------------	--------

**Air Intake System**

Max intake restriction	5.0kPa
------------------------	--------

Combustion air flow	96 m <sup>3</sup> /min
---------------------	------------------------

Air flow required for radiator	1500 m <sup>3</sup> /min
--------------------------------	--------------------------

Comprehensive Solutions For

**POWER GENERATION**

**MODEL: HC-1250GF**

**400V | 1500rpm | 50Hz**

**Fuel System**

Fuel consumption @ 100% (Prime Power) Load	206 g/kWh	238 L/h
Fuel consumption @ 75% (Prime Power) Load	202 g/kWh	176 L/h
Fuel consumption @ 50% (Prime Power) Load	204 g/kWh	122 L/h

**Oil System**

Total oil capacity	153L
Oil consumption	0.4g/kWh
Oil sump capacity	127-153L

**Cooling System**

Coolant capacity	170L
Max water temperature	98°C

**MODEL: HC-1250GF**

**400V | 1500rpm | 50Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	1150kVA
Alternator Efficiency	95.5%

**MODEL: HC-1250GF**

**400V | 1500rpm | 50Hz**

## GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

## STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	

**MODEL: HC-1250GF**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 4650×2060×2300 mm

Weight: 7800 kg



**Soundproof Type (standard 20'ft GP container)**

Overall Dimensions: 6058×2438×2591 mm

Weight: 12800 kg

*Specifications are subject to change without notice.*