


**MODEL: HC-34GF**

**400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>33 kVA</b>	<b>PRP</b> Prime Power	<b>30 kVA</b>
<b>ENGINE</b>	<b>Perkins</b> <b>1103A-33G</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b> <b>SOL2-P1</b>

## GENERAL FEATURES

Engine: Perkins 1103A-33G

Alternator: single bearing, IP23, insulation class H

50°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: HC-34GF****400V | 1500rpm | 50Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF ( COS $\Phi$ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	43	26.4kW/33kVA	24kW/30kVA
415/240	50	3	0.8	46	26.4kW/33kVA	24kW/30kVA
400/230	50	3	0.8	48	26.4kW/33kVA	24kW/30kVA
380/220	50	3	0.8	50	26.4kW/33kVA	24kW/30kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 ( eqv ISO 8528 ) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

Comprehensive Solutions For

**POWER GENERATION**

**MODEL: HC-34GF****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Perkins 1103A-33G
Air intake system	Natural aspirated
Fuel system	Direct Injection
Cylinder arrangement	3 in line
Displacement	3.3L
Bore and stroke	105×127 mm
Compression ratio	19.25:1
Rated speed	1500rpm
Max. Standby power at rated speed	31KW
Governor type	Mechanical

**Exhaust System**

Exhaust gas flow	5.8 m <sup>3</sup> /min
Exhaust temperature	520°C
Max back pressure	10kPa

**Air Intake System**

Max intake restriction	8kPa
Combustion air flow	2.15 m <sup>3</sup> /min
Air flow required for radiator	53 m <sup>3</sup> /min

Comprehensive Solutions For

**POWER GENERATION**

**MODEL: HC-34GF**

**400V | 1500rpm | 50Hz**

**Fuel System**

Fuel consumption @ 100% (Prime Power) Load	211 g/kWh	7.0 L/h
Fuel consumption @ 75% (Prime Power) Load	216 g/kWh	5.2 L/h
Fuel consumption @ 50% (Prime Power) Load	235.4 g/kWh	3.8 L/h

**Oil System**

Total oil capacity	8.3L
Oil consumption as a percentage of full load fuel consumption less than	0.15%(As a percentage of fuel consumption)
Oil sump capacity	6.2-7.8L

**Cooling System**

Coolant capacity	10.2L
Max water temperature	110°C

**MODEL: HC-34GF****400V | 1500rpm | 50Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	30kVA
Alternator Efficiency	87.0%

**MODEL: HC-34GF**

**400V | 1500rpm | 50Hz**

## GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

## STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB
Base fuel tank		

**MODEL: HC-34GF**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 1470×690×1320 mm

Weight: 750 kg



**Soundproof Type**

Overall Dimensions: 1910×880×1450 mm

Weight: 1050 kg

*Specifications are subject to change without notice.*