

**MODEL: HC-360GF2**

**440V | 1800rpm | 60Hz**



<b>ESP</b> Standby Power	<b>352kVA</b>	<b>PRP</b> Prime Power	<b>320kVA</b>
<b>ENGINE</b>	<b>Volvo</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>TAD843GE</b>		<b>S4L1D-D41</b>

## GENERAL FEATURES

Engine: Volvo TAD843GE

Alternator: single bearing, IP23, insulation class H

55°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

**MODEL: HC-360GF2****440V | 1800rpm | 60Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF ( COS $\Phi$ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
480/277	60	3	0.8	423	282kW/352kVA	256kW/320kVA
460/266	60	3	0.8	442	282kW/352kVA	256kW/320kVA
440/254	60	3	0.8	462	282kW/352kVA	256kW/320kVA
416/240	60	3	0.8	489	282kW/352kVA	256kW/320kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

Baifa Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: 15 months from the date BAIFA sold to the first buyer or one year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from Baifa Power or distributors in your location.

**MODEL: HC-360GF2****440V | 1800rpm | 60Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Volvo TAD843GE
Air intake system	Turbocharged, Air/Air inter cooling
Fuel system	Elec. Injection, Elec. Fuel System
Cylinder arrangement	6 in line
Displacement	7.7L
Bore and stroke	110×135 mm
Compression ratio	17.5
Rated speed	1800rpm
Max. Standby power at rated speed	301kW
Governor type	ECU EMS2

**Exhaust System**

Exhaust gas flow	53 m <sup>3</sup> /min
Exhaust temperature	459°C
Max back pressure	10kPa

**Air Intake System**

Max intake restriction	5kPa
Combustion air flow	21.9 m <sup>3</sup> /min
Air flow required for radiator	360 m <sup>3</sup> /min

**MODEL: HC-360GF2****440V | 1800rpm | 60Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	204g/kWh	71L/h
Fuel consumption @ 75% (Prime Power) Load	204g/kWh	54L/h
Fuel consumption @ 50% (Prime Power) Load	214g/kWh	39L/h

**Oil System**

Total oil capacity	27L
Oil consumption	0.02L/h
Oil sump capacity	16-25L

**Cooling System**

Coolant capacity	41L
Max water temperature	107°C

**MODEL: HC-360GF2****440V | 1800rpm | 60Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	370kVA
Alternator Efficiency	92.9%

**MODEL: HC-360GF2****440V | 1800rpm | 60Hz****GENERATING SET DATA**

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
Transient voltage deviation (sudden power increase)	$\leq -15\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
Voltage recovery time (sudden power increase)	$\leq 4S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 0.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
Transient frequency deviation (sudden power increase)	$\leq -7\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
Frequency recovery time (sudden power increase)	$\leq 3S$

**STANDARD FEATURES**

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB

Base fuel tank


**MODEL: HC-360GF2**

**440V | 1800rpm | 60Hz**

## OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


## DIMENSIONS & WEIGHT



### Standard Configuration (open type)

Overall Dimensions: 2870×1050×1610 mm

Weight: 2500 kg



### Soundproof Type

Overall Dimensions: 3890×1460×2150 mm

Weight: 4000 kg

*Specifications are subject to change without notice.*