

MODEL: HC-BD3100

400V | 1500rpm | 50Hz



ESP Standby Power	3125 kVA	PRP Prime Power	2813 kVA
ENGINE	Baudouin	ALTERNATOR	LEROY SOMER
	16M55G0D3/5		LSA 53.2 M9

GENERAL FEATURES

Engine: Baudouin 16M55G0D3/5

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

MODEL: HC-BD3100

400V | 1500rpm | 50Hz

GENERATOR RATINGS

Voltage	Hz	Phase	PF (COSΦ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	4101	2500kW/3125kVA	2250kW/2813kVA
415/240	50	3	0.8	4348	2500kW/3125kVA	2250kW/2813kVA
400/230	50	3	0.8	4511	2500kW/3125kVA	2250kW/2813kVA
380/220	50	3	0.8	4748	2500kW/3125kVA	2250kW/2813kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

MODEL: HC-BD3100**400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Baudouin 16M55G0D3/5
Air intake system	Turbo, intercooling
Fuel system	High Pressure Common Rail
Cylinder arrangement	16 cylinders in V
Displacement	87.5 L
Bore and stroke	180×215 mm
Compression ratio	16.5:1
Rated speed	1500rpm
Max. Standby power at rated speed	2750KW
Governor type	ECU

Exhaust System

Exhaust gas flow	606 m ³ /min
Exhaust temperature	N/A
Max back pressure	15 kPa

Air Intake System

Max intake restriction	7 kPa
Combustion air flow	184 m ³ /min
Air flow required for radiator	3000 m ³ /min

MODEL: HC-BD3100**400V | 1500rpm | 50Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	191.8g/kWh	546 L/h
Fuel consumption @ 75% (Prime Power) Load	195.6g/kWh	422 L/h
Fuel consumption @ 50% (Prime Power) Load	205.4g/kWh	302 L/h

Oil System

Total oil capacity	582L
Oil consumption ratio based on fuel consumption data	$\leq 0.2\text{g/kW}\cdot\text{h}$
Oil sump capacity	405-500L

Cooling System

Coolant capacity	350L(without radiator)
Max water temperature	103°C

MODEL: HC-BD3100

400V | 1500rpm | 50Hz

ALTERNATOR SPECIFICATION

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	3000kVA
Alternator Efficiency	96.3%

MODEL: HC-BD3100 **400V | 1500rpm | 50Hz**

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +20\%$
Transient voltage deviation (sudden power increase)	$\leq -15\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 4S$
Voltage recovery time (sudden power increase)	$\leq 4S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 0.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +10\%$
Transient frequency deviation (sudden power increase)	$\leq -7\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 3S$
Frequency recovery time (sudden power increase)	$\leq 3S$

STANDARD FEATURES


Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	

MODEL: HC-BD3100 **400V | 1500rpm | 50Hz**

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

DIMENSIONS & WEIGHT



Standard Configuration (open type)
Overall Dimensions: 7250×2500×3000 mm
Weight: 24000 kg

Specifications are subject to change without notice.