


MODEL: HC-BD440 **400V | 1500rpm | 50Hz**



ESP Standby Power	440 kVA	PRP Prime Power	400 kVA
ENGINE	Baudouin	ALTERNATOR	STAMFORD
	6M21G440/5		S4L1D-F41

GENERAL FEATURES

Engine: Baudouin 6M21G440/5	Alternator: single bearing, IP23, insulation class H
40°C radiator, fans are driven by belt, with safety guard	Dry type air filter, fuel filter & oil filter
Vibration damper	Standard control panel
24V charging alternator	Exhaust bellows, elbows, flange & muffler
Lead-acid batteries, rack and cables	User manual

MODEL: HC-BD440**400V | 1500rpm | 50Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF (COS Φ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	577	352kW/440kVA	320kW/400kVA
415/240	50	3	0.8	612	352kW/440kVA	320kW/400kVA
400/230	50	3	0.8	635	352kW/440kVA	320kW/400kVA
380/220	50	3	0.8	669	352kW/440kVA	320kW/400kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

MODEL: HC-BD440**400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Baudouin 6M21G440/5
Air intake system	Turbo, intercooling
Fuel system	Mechanical pump
Cylinder arrangement	6 cylinders in line
Displacement	12.54 L
Bore and stroke	127×165 mm
Compression ratio	16:1
Rated speed	1500rpm
Max. Standby power at rated speed	405KW
Governor type	Electronic

Exhaust System

Exhaust gas flow	69 m ³ /min
Exhaust temperature	580°C
Max back pressure	12 kPa

Air Intake System

Max intake restriction	7 kPa
Combustion air flow	26.7 m ³ /min
Air flow required for radiator	398 m ³ /min

MODEL: HC-BD440**400V | 1500rpm | 50Hz****Fuel System**

Fuel consumption @ 100% (Prime Power) Load	195.1 g/kWh	83.6 L/h
Fuel consumption @ 75% (Prime Power) Load	193.4 g/kWh	62.7 L/h
Fuel consumption @ 50% (Prime Power) Load	197.1 g/kWh	44.2 L/h

Oil System

Total oil capacity	32L
Oil consumption ratio based on fuel consumption data	≤ 0.2%
Oil sump capacity	27~30L

Cooling System

Coolant capacity	45L
Max water temperature	105°C

MODEL: HC-BD440**400V | 1500rpm | 50Hz**

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	415kVA
Alternator Efficiency	93.2%

MODEL: HC-BD440**400V | 1500rpm | 50Hz****GENERATING SET DATA**

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB


MODEL: HC-BD440

400V | 1500rpm | 50Hz


OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

DIMENSIONS & WEIGHT



Standard Configuration (open type)
Overall Dimensions: 2950×1110×1730 mm
Weight: 3080 kg



Soundproof Type
Overall Dimensions: 4230×1460×2150 mm
Weight: 4430 kg

Specifications are subject to change without notice.