


MODEL: HC-BD710-60

440V | 1800rpm | 60Hz



ESP Standby Power	712kVA	PRP Prime Power	650kVA
ENGINE	Baudouin	ALTERNATOR	STAMFORD
	6M33G575/6		S5L1D-E41

GENERAL FEATURES

Engine: Baudouin 6M33G575/6

Alternator: single bearing, IP23, insulation class H

40°C radiator, fans are driven by belt, with safety guard

Dry type air filter, fuel filter & oil filter

Vibration damper

Standard control panel

24V charging alternator

Exhaust bellows, elbows, flange & muffler

Lead-acid batteries, rack and cables

User manual

MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

GENERATOR RATINGS

Voltage	Hz	Phase	PF (COS Φ)	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
480/277	60	3	0.8	856	570kW/712kVA	520kW/650kVA
460/266	60	3	0.8	894	570kW/712kVA	520kW/650kVA
440/254	60	3	0.8	934	570kW/712kVA	520kW/650kVA
416/240	60	3	0.8	988	570kW/712kVA	520kW/650kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

SALES PROMISES

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

ENGINE SPECIFICATION

Manufacturer / Model	Baudouin 6M33G575/6
Air intake system	Turbocharged and Aftercooled
Fuel system	Mechanical Pump
Cylinder arrangement	6 in line
Displacement	19.6L
Bore and stroke	150 × 185 mm
Compression ratio	15
Rated speed	1800rpm
Max. Standby power at rated speed	633kW
Governor type	Electronic

Exhaust System

Exhaust gas flow	148.0m ³ /min
Exhaust temperature	550°C
Max back pressure	7.5kPa

Air Intake System

Max intake restriction	6.5kPa
Combustion air flow	48.3 m ³ /min
Air flow required for radiator	954 m ³ /min

MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

Fuel System

Fuel consumption @ 100% (Prime Power) Load	203.0g/kWh	137L/h
Fuel consumption @ 75% (Prime Power) Load	198.3g/kWh	102L/h
Fuel consumption @ 50% (Prime Power) Load	205.1g/kWh	72L/h

Oil System

Total oil capacity	64L
Oil sump capacity	36-61L
Oil fuel consumption ratio based on engine fuel consumption data	≤ 0.3%

Cooling System

Coolant capacity	160L
Max water temperature	103°C

MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	< 50
THF	< 2%
Alternator Capacity	713kVA
Alternator Efficiency	94.9%

MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB



MODEL: HC-BD710-60

440V | 1800rpm | 60Hz

OPTIONS

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		

DIMENSIONS & WEIGHT



Standard Configuration (open type)

Overall Dimensions: 3750×1640×2050 mm

Weight: 5320 kg

Soundproof Type

Overall Dimensions: 5530×1860×2550 mm

Weight: 7320 kg

Specifications are subject to change without notice.