

**MODEL: HC-BD880** **400V | 1500rpm | 50Hz**



<b>ESP</b> Standby Power	<b>880 kVA</b>	<b>PRP</b> Prime Power	<b>800 kVA</b>
<b>ENGINE</b>	<b>Baudouin</b>	<b>ALTERNATOR</b>	<b>STAMFORD</b>
	<b>8M33G900/5</b>		<b>S6L1D-C4</b>

**GENERAL FEATURES**

Engine: Baudouin 8M33G900/5	Alternator: single bearing, IP23, insulation class H
40°C radiator, fans are driven by belt, with safety guard	Dry type air filter, fuel filter & oil filter
Vibration damper	Standard control panel
24V charging alternator	Exhaust bellows, elbows, flange & muffler
Lead-acid batteries, rack and cables	User manual

**MODEL: HC-BD880****400V | 1500rpm | 50Hz****GENERATOR RATINGS**

Voltage	Hz	Phase	PF ( COS $\Phi$ )	Standby Amps	Standby Ratings (kW / kVA)	Prime Ratings (kW / kVA)
440/254	50	3	0.8	1155	704kW/880kVA	640kW/800kVA
415/240	50	3	0.8	1224	704kW/880kVA	640kW/800kVA
400/230	50	3	0.8	1270	704kW/880kVA	640kW/800kVA
380/220	50	3	0.8	1337	704kW/880kVA	640kW/800kVA

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO 8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

**SALES PROMISES**

HiChai Power provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: One year after installation or 1000 running hours (accumulated), whichever comes first.

Service and parts are available from HiChai Power or distributors in your location.

**MODEL: HC-BD880****400V | 1500rpm | 50Hz****ENGINE SPECIFICATION**

Manufacturer / Model	Baudouin 8M33G900/5
Air intake system	Turbo, intercooling
Fuel system	Mechanical pump
Cylinder arrangement	8 cylinders in V
Displacement	26 L
Bore and stroke	150×185 mm
Compression ratio	15:1
Rated speed	1500rpm
Max. Standby power at rated speed	800KW
Governor type	Electronic

**Exhaust System**

Exhaust gas flow	150 m <sup>3</sup> /min
Exhaust temperature	550°C
Max back pressure	7.5 kPa

**Air Intake System**

Max intake restriction	6.2 kPa
Combustion air flow	47 m <sup>3</sup> /min
Air flow required for radiator	1140 m <sup>3</sup> /min



**MODEL: HC-BD880**

**400V | 1500rpm | 50Hz**

**Fuel System**

Fuel consumption @ 100% (Prime Power) Load	200.5 g/kWh	167 L/h
Fuel consumption @ 75% (Prime Power) Load	199 g/kWh	125 L/h
Fuel consumption @ 50% (Prime Power) Load	206.3 g/kWh	89 L/h

**Oil System**

Total oil capacity	110L
Oil consumption ratio based on fuel consumption data	≤ 0.3 %
Oil sump capacity	90-105L

**Cooling System**

Coolant capacity	163L
Max water temperature	101°C

**MODEL: HC-BD880****400V | 1500rpm | 50Hz**

## ALTERNATOR SPECIFICATION

Industrial alternators meet the requirements of the relevant parts of the BS5000, VDE 0530, NEMA MG1-22, IEC34, CSA 22.2-100 and AS1359.

### Alternator Data

Number of Phase	3
Connecting Type	3 Phase and 4 Wires, Y type connecting
Number of Bearing	1
Power Factor	0.8
Protection Class	IP23
Altitude	≤1000m
Exciter Type	Brushless exciting
Insulation Class/Temperature Rise	H/H
Telephone Influence Factor (TIF)	<50
THF	<2%
Alternator Capacity	810kVA
Alternator Efficiency	94.4%

**MODEL: HC-BD880**

**400V | 1500rpm | 50Hz**

### GENERATING SET DATA

Related range of voltage setting	$\geq \pm 5\%$
Steady-state voltage deviation	$\leq \pm 1\%$
Transient voltage deviation (100 % sudden power decrease)	$\leq +25\%$
Transient voltage deviation (sudden power increase)	$\leq -20\%$
Voltage recovery time (100 % sudden power decrease)	$\leq 6S$
Voltage recovery time (sudden power increase)	$\leq 6S$
Related range of frequency setting	0-5% adjustable
Steady-state frequency band	$\leq 1.5\%$
Transient frequency deviation (100 % sudden power decrease)	$\leq +12\%$
Transient frequency deviation (sudden power increase)	$\leq -10\%$
Frequency recovery time (100 % sudden power decrease)	$\leq 5S$
Frequency recovery time (sudden power increase)	$\leq 5S$

### STANDARD FEATURES

Standard auto control system	Exhaust system (including until muffler)	Documents
Oil drain valve	Starting batteries (maintenance-free & watering-free) with connective wires	MCCB


**MODEL: HC-BD880**

**400V | 1500rpm | 50Hz**

**OPTIONS**

Daily fuel tank	Rainproof type	Remote control panel
Alternator heater	Soundproof type	Paralleling system
Spare parts	Trailer type	Switch box
Automatic transfer switch		


**DIMENSIONS & WEIGHT**



**Standard Configuration (open type)**

Overall Dimensions: 3900×1735×2210mm

Weight: 6600 kg



**Soundproof Type (standard 20'ft HQ container)**

Overall Dimensions: 6058×2438×2896 mm

Weight: 11600 kg

*Specifications are subject to change without notice.*